

REVISIONS:

GENERAL NOTES

- DO NOT SCALE FROM THESE DRAWINGS. DIMENSIONS SHALL BE TAKEN FROM ARCHITECTURAL DRAWINGS.
- THESE DRAWINGS ARE DIAGRAMMATIC AND ARE INTENDED ONLY TO DEFINE THE BASIC FUNCTIONS REQUIRED. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO FURNISH ALL SPECIFICATIONS OF THE SYSTEMS, EQUIPMENT AND ACCESSORIES INDICATED. SHALL BE INCLUDED AND INSTALLED. SUCH ACCESSORIES MAY INCLUDE, BUT NOT LIMITED TO, FILTERS, CONDENSATE DRAINS, RELIEF VALVES, SERVICE VALVES, THERMOSTATS, VIBRATION ISOLATORS, MOTOR STARTERS, ETC.
- SCOPE OF WORK CONSISTS OF FURNISHING LABOR, MATERIALS AND EQUIPMENT FOR THE INSTALLATION. IT ALSO INCLUDES PLACING INTO OPERATION COMPLETE AND OPERABLE HEATING, VENTILATING AND AIR CONDITIONING SYSTEMS AS SPECIFIED AND SHOWN. THIS INCLUDES, BUT IS NOT LIMITED TO: HVAC UNITS, EXHAUST FANS, DUCTLESS SPLIT-SYSTEMS, DUCTWORK, AIR DISTRIBUTION CONTROLS AND ACCESSORIES.
- ALL REQUIRED OFFSETS, RISERS AND PROPS DUE TO POSSIBLE OBSTRUCTIONS OF DUCT AND PIPE RUNS ARE NOT NECESSARILY SHOWN. MECHANICAL CONTRACTOR SHALL INCLUDE A CONTINGENCY IN HIS BID TO OFFSET ANY COST REQUIRED FOR ADDITIONAL FITTINGS AND LABOR THAT MAY BE REQUIRED. MINOR DEVIATIONS FROM THE DESIGN LAYOUT IN ROUTING THE DUCT AND/OR PIPING ARE ANTICIPATED AND SHALL BE CONSIDERED A PART OF THE WORK INCLUDED. THE CONTRACTOR SHALL VERIFY THE ACTUAL DIMENSIONS OF THE EQUIPMENT PROPOSED TO ENSURE THAT THE EQUIPMENT WILL FIT IN THE AVAILABLE SPACE.
- HVAC LAYOUT IS BASED ON ARCHITECTURAL DRAWINGS AVAILABLE AT TIME OF DESIGN. AS STRUCTURAL OR OTHER FIELD CONDITIONS MAY OCCUR, CONTRACTOR IS RESPONSIBLE TO FIND VERTICAL LOCATION OF THE HVAC DUCTWORK AND DUCTWORK COORDINATE WITH THE ARCHITECT/ENGINEER. SHALL NOT MAKE CHANGES OR ANY REQUIRED ALTERATIONS, EITHER CONTRACTOR OR OWNER SHALL TAKE RESPONSIBILITY FOR VERIFYING THE INTEGRITY OF THE CHANGES WITH THE HVAC DESIGN ENGINEER.
- ALL WORK SHALL BE INSTALLED IN ACCORDANCE WITH THE REQUIREMENTS OF ALL APPLICABLE CODES AND REGULATIONS INCLUDING, BUT NOT LIMITED TO, NATIONAL, STATE, AND LOCAL ORDINANCES WHICH MAY BE IN EFFECT. ALL HVAC MATERIALS, INSTALLATION PROCEDURES AND SYSTEM LAYOUTS SHALL BE APPROVED BY ALL APPLICABLE CODE ENFORCEMENT AUTHORITIES HAVING JURISDICTION. THE MECHANICAL CONTRACTOR SHALL PROVIDE ALL MATERIALS AND LABOR NECESSARY TO COMPLY WITH THESE RULES, REGULATIONS AND ORDINANCES. NO ADDITIONAL CHARGES FOR COMPLYING WITH UNACCEPTABLE REQUIREMENTS, THEREFORE, WHICH CHANGES AND/OR SPECIFICATIONS INDICATE MATERIALS OR CONSTRUCTION IN EXCESS OF THESE CODE REQUIREMENTS, THE DRAWINGS AND/OR SPECIFICATIONS SHALL GOVERN.
- IT IS THE RESPONSIBILITY OF THE MECHANICAL CONTRACTOR TO PAY FOR ALL NECESSARY PERMITS AND APPROVALS FOR THIS INSTALLATION.
- IT IS THE RESPONSIBILITY OF THE MECHANICAL CONTRACTOR TO REVIEW THESE PLANS AND SPECIFICATIONS, AS WELL AS THE RELATED PLUMBING, FIRE PROTECTION, ELECTRICAL, STRUCTURAL, ARCHITECTURAL, INTERIOR DECOR AND SITE ENGINEERING DRAWINGS TO BECOME FAMILIAR WITH THE FULL PROJECT SCOPE. IN ADDITION, THE MECHANICAL CONTRACTOR MUST COORDINATE WITH ANY OTHER CONTRACTORS LISTED ON THE DRAWINGS AND ALL REQUIREMENTS WHICH MAY NOT BE SPECIFIED HEREIN AND WHICH THE OWNER MAY CONSIDER PART OF THIS CONTRACT. DURING THE COURSE OF CONSTRUCTION COORDINATION AND ACTUAL CONSTRUCTION, IT IS THE RESPONSIBILITY OF THE MECHANICAL CONTRACTOR TO WORK CLOSELY WITH ALL ACCOMPANYING CONTRACTORS AND TRADESMEN IN ORDER TO ENSURE A SMOOTH RUNNING AND CAREFULLY COORDINATED INSTALLATION.
- ANY DISCREPANCIES OR INADEQUACIES WITHIN THESE BID DOCUMENTS OR BETWEEN THESE BID DOCUMENTS AND THE RELATED PLUMBING, FIRE PROTECTION, ELECTRICAL, STRUCTURAL, ARCHITECTURAL, INTERIOR DECOR AND SITE ENGINEERING DRAWINGS, OR BETWEEN THESE BID DOCUMENTS AND FIELD CONDITIONS MUST BE BROUGHT TO THE ATTENTION OF THE OWNER, ARCHITECT/ENGINEER PRIOR TO BID SUBMISSION.
- THE MECHANICAL CONTRACTOR SHALL FURNISH AND INSTALL NEW PRODUCTS OF ESTABLISHED AND REPUTABLE MANUFACTURERS. NO EQUIPMENT SUBSTITUTIONS SHALL BE MADE THAT WOULD LEAVE THE CONTRACTOR IN A POSITION TO SELL SUBSTANTIALLY LOWER PRICED EQUIPMENT. THE CONTRACTOR SHALL FOLLOW MANUFACTURER'S RECOMMENDED INSTALLATION PROCEDURES AND IN AN ARRANGEMENT THAT WILL GIVE THE GREATEST PRACTICAL EASE OF OPERATION AND SERVICE TO THE OWNER. MATERIALS AND EQUIPMENT SHALL BE INSTALLED SQUARELY WITH THE BUILDING LINES.
- CONSTRUCT AND BRACE EQUIPMENT, PIPING, ETC., SO THAT THERE WILL BE NO VIBRATION AND/OR RATTLING WHEN THE SYSTEM IS IN OPERATION.
- SPECIFIC REFERENCE TO A MANUFACTURER'S PRODUCT IS ONLY TO ESTABLISH TYPE, QUALITY, AND PERFORMANCE REQUIRED. THESE QUALIFICATIONS ARE IN ADDITION TO THE REQUIREMENTS SHOWN ON THE PLANS.
- FABRICATE, SUPPORT, TEST AND INSTALL ALL DUCTWORK IN STRICT ACCORDANCE WITH THE LATEST EDITION OF THE SMACNA H.V.A.C. DUCT CONSTRUCTION STANDARDS METAL AND FLEXIBLE - SECOND EDITION AND ALL APPLICABLE BUILDING CODES.
- RETURN AIR DUCT TO HAVE AT LEAST ONE (1) 90° ELBOW BETWEEN THE PLENUM ON THE FAU TO THE PLENUM AT THE RETURN AIR GRILLE. PLENUM BOX AT RETURN AIR GRILLE TO BE A MINIMUM 6" DEEP. RETURN AIR GRILLES TO BE A MINIMUM OF 3" DISTANCE FROM SMOKE DETECTORS.
- ALL OUTSIDE AIR INTAKES SHALL BE LOCATED A MINIMUM OF 10' FROM ANY PLUMBING VENT, EXHAUST, AND FLUE OUTLETS.
- EXHAUST DUCTS SHALL TERMINATE THREE (3) FEET FROM ANY BUILDING OPENING AND BE EQUIPPED WITH A BACKDRAFT DAMPER. SHALL NOT BE INSTALLED AT THE DUCT TERMINATION.
- ALLOW 24° TO 36° OF STRAIGHT RUN FROM FAN OUTLET POINT BEFORE ADDING AN ELBOW OR BEND TO EXHAUST DUCTWORK.
- FLASH AND COUNTER FLASH ALL ROOF PENETRATIONS. COORDINATE INSTALLATION OF ALL ROOF FLASHING AT ROOF PENETRATION.
- SEAL ALL REFRIGERATION LINE PENETRATIONS AIR AND WATER TIGHT w/ SILICONE SEALANT.
- MECHANICAL CONTRACTOR SHALL BE RESPONSIBLE FOR TESTING, ADJUSTING, AND BALANCING (T.A.B.) T.A.B. WORK SHALL INCLUDE THE ENTIRE AIR-SIDE SYSTEM AND BE PERFORMED IN ACCORDANCE WITH NEBB OR AACB REQUIREMENTS. TOLERANCES FOR AIR INLETS AND OUTLETS SHALL BE +/- 5% UNLESS NOTED OTHERWISE.
- CONTRACTOR SHALL INSPECT ANY EXISTING DUCTWORK FOR DEFECTS AND REPORT TO THE ARCHITECT/ENGINEER AND THE OWNER ANY DEFICIENCIES PRIOR TO PERFORMING ANY WORK. CONTRACTOR

HVAC LEGEND

SYMBOL	DESCRIPTION
	ELBOW UP DIMENSION DESCRIPTION: 14" x 20" ROUND DUCT 24x12 FO = FLAT OVAL DUCT
	ELBOW DOWN
	LONG RADIUS ELBOW RADIUS (R) = 1.5 TIMES DIAMETER OF DUCT
	SUPPLY AIR ELBOW UP DIMENSION DESCRIPTION: 1ST FIGURE = SIDE SHOWN 2ND FIGURE = SIDE NOT SHOWN
	SUPPLY AIR ELBOW DOWN
	EXHAUST/RETURN AIR ELBOW UP
	EXHAUST/RETURN AIR ELBOW DOWN
	DOUBLE SIDE TRANSITION TRANSITION SLOPE SPECIFICATION: MINIMUM SLOPE = 15° MAXIMUM SLOPE = 45°
	SINGLE SIDE TRANSITION
	TOP TRANSITION (SLOPE ON TOP)
	BOTTOM TRANSITION (SLOPE ON BOTTOM)
	ACOUSTICALLY LINED SHEET METAL DUCT
	MANUAL BALANCING DAMPER
	FLEX CONNECTOR
	ACCESS DOORS
	FIRE DAMPER, FIRE/SMOKE DAMPER, SMOKE DAMPER
	MOTORIZED DAMPER
NOTE: NOT ALL SYMBOLS MAY BE USED	
	TURNING VANE ELBOW
	45° LOW-LOSS TAKE-OFF FITTING W/ DAMPER & FLEX DUCT
	45° LOW-LOSS TAKE-OFF FITTING W/ DAMPER & RIGID DUCT
	90° TEE TAKE-OFF FITTING
	CONICAL 90° TEE TAKE-OFF FITTING
	45° TEE TAKE-OFF FITTING
	LOW LOSS TAKE-OFF FITTING
	SUPPLY AIR DUCT (SINGLE LINE)
	RETURN AIR DUCT (SINGLE LINE)
	EXHAUST AIR DUCT (SINGLE LINE)
	RETURN AIR GRILLE
	EXHAUST AIR GRILLE
	SIDE WALL SUPPLY AIR REGISTER
	DIFFUSER, REGISTER OR GRILLE 4-WAY THROW PATTERN UNLESS SHOWN OTHERWISE ON DRAWINGS
	RTU-1 THERMOSTAT - CONTROLLED EQUIPMENT NOTED

STANDARD ABBREVIATIONS

AC	AIR CONDITIONING UNIT	ET	EXPANSION TANK	NTS	NOT TO SCALE
AD	ACCESS DOOR	EWB	ENTERING WET BULB	OA	OUTSIDE AIR
AFF	Above Finished Floor	EWT	ENTERING WATER TEMPERATURE	ODD	OUTDOOR AIR DAMPER
AHU	AIR HANDLING UNIT	EXH	EXHAUST	PD	PRESSURE DROP
AMB	AMBIENT	FPM	FEET PER MINUTE	PSI	POUNDS/SQUARE INCH
APD	AIR PRESSURE DROP	FT	FEET OR FOOT	RA	RETURN AIR
APPROX	APPROXIMATE	GPM	GALLONS PER MINUTE	RH	RELATIVE HUMIDITY
AVG	AVERAGE	HP	HORSEPOWER	RTU	REMOVABLE AIR UNIT
BDD	BACK DRAFT DAMPER	HWS	HOT WATER RETURN	SA	SUPPLY AIR
BHD	Brake Horse Power	HWT	HOT WATER SUPPLY	FSD	FIRE/SMOKE DAMPER
BTU/H	BTU/H THERMAL UNIT/HOUR	HX	HOT TEE EXCHANGER	SP	STATIC PRESSURE
CAP	CAPACITY	IN	INCHES	SPEC	SPECIFICATIONS
CFM	CUBIC FEET PER MINUTE	INWG	INCHES IN WATER GAUGE	SL	SEA LEVEL
CU	CONDENSING UNIT	INWC	INCHES IN WATER COLUMN	SQ	SQUARE
CP	CONDENSATE PUMP	LAT	LEAVING AIR TEMPERATURE	SS	STAINLESS STEEL
CWH	CABINET WATER HEATER	LWT	LEAVING WATER TEMPERATURE	T.A.B.	TEST AND BALANCING
CC	CLOUDING COIL	MAU	MAKEUP AIR UNIT	TEMP	TEMPERATURE
D/DIA	DIAMETER	MAX	MAXIMUM	TSP	TOTAL STATIC PRESSURE
DB	DRY BULB TEMPERATURE	MBH	MANUFACTURED DAMPER	T-STAT	THERMOSTAT
DEG.	DEGREES	MD	MANUFACTURER	TYP	TYPE
D.L.	DUCT LINER	MIN	MINIMUM	UV	ULTRAVIOLET
(E)	EXISTING	MVR	MANUAL VOLUME DAMPER	VAV	VARIABLE AIR VOLUME
EA	EXHAUST AIR	MVD	MANUAL VOLUME DAMPER	VEL	VELOCITY
EAT	ENTERING AIR TEMPERATURE	(N)	NEW	VFD	VARIABLE FREQUENCY DRIVE
EDB	ENTERING DRY BULB	NA	NOT APPLICABLE	W	WATER
EFT	EVAPORATION	NIC	NOT IN CONTRACT	WB	WET BULB
ELECT	ELECTRICAL	NC	NORMALLY CLOSED	WPD	WATER PRESSURE DROP
ELEV	ELEVATION	NO	NORMALLY OPENED	WMS	WIRE MESH SCREEN
ESP	EXTERNAL STATIC PRESSURE	NOM	NOMINAL		

SHEET INDEX

SHEET NUMBER	SHEET TITLE	CD
M0.01	GENERAL INFORMATION	04/25/2016
M0.04	DEMO FLOOR PLAN	
M1.01	FLOOR PLAN	

KGA ARCHITECTURE

1701 Directon Boulevard, Suite 770
Austin, Texas 78744
512.441.8200
www.KGArchitects.com
LAS VEGAS

CONSULTANTS:
MECHANICAL / PLUMBING / ELECTRICAL
TJK CONSULTING ENGINEERS, INC.
PHONE 070-671-3621

PROJECT:
UNLV MARYLAND
ADMINISTRATIVE BUILDING
TENANT IMPROVEMENT


SHEET CONTENTS:
GENERAL INFORMATION

DATE: APRIL 25, 2016
JOB NO: 16323.00
SHEET:

M0.01



TJK # 15122



REVISIONS

UNLV

MARYLAND ADMINISTRATIVE BUILDING I TENANT IMPROVEMENT

KGA ARCHITECTURE
1701 Directon Boulevard, Suite 770
Austin, Texas 78744
512.441.8200
www.kgarchitects.com

CONSULTANTS:
MECHANICAL / PLUMBING / ELECTRICAL
TJK CONSULTING ENGINEERS, INC.
PHONE 702.871.3621
www.tjkengineering.com

PROJECT:
UNLV MARYLAND
ADMINISTRATIVE BUILDING I
TENANT IMPROVEMENT

Sheet Contents:
DEMO FLOOR PLAN

DATE:
APRIL 25, 2016
Job No.:
16323.00
Sheet:

M0.04




5459 S. Durango Dr., Suite 100
Las Vegas, NV 89113
P: 702.871.3621
F: 702.871.8353
www.tjkengineering.com
TJK # 15122


GENERAL NOTES:

1. MECHANICAL CONTRACTOR SHALL FIELD VERIFY ALL EXISTING CONDITIONS PRIOR TO START.
2. COORDINATE ALL MECHANICAL WORK FOR POTENTIAL CONFLICTS WITH OTHER TRADES.
3. UNLESS OTHERWISE NOTED ALL MECHANICAL EQUIPMENT, DUCTWORK, AND AIR TERMINALS SHALL REMAIN.

KEY NOTES: (B)

1. CLEAN AND REUSE EXISTING DIFFUSERS AND GRILLES IN SAME LOCATION.
2. CLEAN AND REUSE EXISTING DIFFUSERS AND GRILLES IN NEW LOCATION. SEE SHEET M1.01 FOR NEW LOCATION.
3. T-STAT TO BE REMOVED AND REPLACED IN SAME LOCATION.
4. T-STAT TO BE REMOVED AND REPLACED IN NEW LOCATION. SEE SHEET M1.01 FOR NEW LOCATION.





REVISIONS

GENERAL NOTES:

1. POSITION ALL UNITS & FANS TO PROVIDE ADEQUATE CLEARANCE FOR MAINTENANCE PER CODE.
2. COORDINATE ALL MECHANICAL WORK FOR POTENTIAL CONFLICTS WITH OTHER TRADES.
3. MAIN DUCT PENETRATIONS SHALL BE FULL SIZE RIGID SHEET METAL DOWN BELOW ROOF WITH ADEQUATE LENGTH TO ATTACH DUCT RUNS AND SMOKE DETECTOR.
4. ALL EXPOSED DUCTWORK SHALL BE RIGID SHEET METAL. ALL OTHER SUPPLY AND RETURN DUCTWORK MAY BE FLEXIBLE DUCTWORK. ALL EXHAUST DUCT SHALL BE RIGID SHEET METAL.

KEY NOTES:

1. CLEAN AND REUSE EXISTING DIFFUSER OR GRILLE IN SAME LOCATION.
2. CLEAN AND REUSE EXISTING DIFFUSER OR GRILLE IN NEW LOCATION. SHIFT DIFFUSER OR GRILLE LOCATION IN GRID AND EXTEND CORRESPONDING FLEX DUCT AS NECESSARY.
3. PROVIDE NEW PROGRAMMABLE T-STAT IN EXISTING LOCATION. PROVIDE ALTERNATE BID FOR WIFI ENABLED PROGRAMMABLE T-STAT.
4. PROVIDE NEW PROGRAMMABLE T-STAT IN NEW LOCATION. PROVIDE ALTERNATE BID FOR WIFI ENABLED PROGRAMMABLE T-STAT.

UNLV
MARYLAND ADMINISTRATIVE BUILDING I
TENANT IMPROVEMENT

KGA ARCHITECTURE
1701 Directon Boulevard, Suite 770
Austin, Texas 78744
512.441.8200
www.kgarchitects.com
LAS VEGAS


CONSULTANTS:
MECHANICAL / PLUMBING / ELECTRICAL
TJK CONSULTING ENGINEERS, INC.
PHONE: 702.871.8321
www.tjkengineers.com

PROJECT:
UNLV MARYLAND
ADMINISTRATIVE BUILDING I
TENANT IMPROVEMENT

JK
tjk consulting engineers, inc.
5459 S. Durango Dr., Suite 100
Las Vegas, NV 89113
P: 702.871.3621
F: 702.871.8353
www.tjkengineers.com
TJK # 15122

DATE:
APRIL 25, 2016
JOB NO:
16323.00
SHEET:

M1.01



GENERAL NOTES

- DO NOT SCALE FROM THESE DRAWINGS. DIMENSIONS SHALL BE TAKEN FROM ARCHITECTURAL DRAWINGS.
- THESE DRAWINGS ARE DIAGRAMMATIC AND ARE INTENDED ONLY TO DEFINE THE BASIC FUNCTIONS REQUIRED.
- THE SCOPE OF INCLUDED WORK CONSISTS OF FURNISHING LABOR, MATERIALS, AND EQUIPMENT FOR THE INSTALLATION. IT ALSO INCLUDES DRAINS, VENTS, OPERATING, COMPLETE AND GENERAL SYSTEMS AS SPECIFIED AND SHOWN. ACCESSORIES REQUIRED FOR PROPER OPERATION OF THE SYSTEM, EVEN THOUGH NOT SPECIFICALLY INDICATED, SHALL BE INCLUDED AND INSTALLED. SUCH ACCESSORIES MAY INCLUDE, BUT ARE NOT LIMITED TO, VALVES, FITTINGS, PIPING SUPPORTS, ETC.
- ALL REQUIRED OFFSETS, RISES AND DROPS DUE TO POSSIBLE OBSTRUCTIONS OF PIPE RUNS ARE NOT NECESSARILY SHOWN. PLUMBING CONTRACTOR SHALL INCLUDE A CONTINGENCY IN HIS BID TO OFFSET ANY COST REQUIRED FOR ADDITIONAL FITTINGS AND LABOR THAT MAY BE REQUIRED.
- PLUMBING LAYOUT REPRESENTED IN THESE DRAWINGS IS BASED ON ARCHITECTURAL DRAWINGS AVAILABLE AT TIME OF DESIGN. AS STRUCTURAL OR OTHER FIELD CHANGES MAY OCCUR, PLUMBING CONTRACTOR IS RESPONSIBLE TO FIELD VERIFY LOCATION OF ALL PLUMBING EQUIPMENT AND PIPING BEFORE INSTALLATION. PLUMBING CONTRACTOR SHALL NOTIFY OWNER OF ANY REQUIRED ALTERATIONS. EITHER CONTRACTOR OR OWNER SHALL TAKE RESPONSIBILITY FOR VERIFYING THE INTEGRITY OF THE CHANGES WITH THE PLUMBING DESIGN ENGINEER.
- ALL WORK SHALL BE INSTALLED IN ACCORDANCE WITH THE REQUIREMENTS OF ALL APPLICABLE CODES AND REGULATIONS INCLUDING BUT NOT LIMITED TO NATIONAL, CITY, STATE AND LOCAL ORDINANCES WHICH MAY BE IN EFFECT. ALL PLUMBING MATERIALS, INSTALLATION PROCEDURES AND SYSTEM LAYOUTS SHALL BE APPROVED BY THE LOCAL PLUMBING INSPECTOR. THE CONTRACTOR SHALL PROVIDE ALL MATERIALS AND LABOR NECESSARY TO COMPLY WITH THESE RULES, REGULATIONS AND ORDINANCES AT NO ADDITIONAL COST. THESE CODES REPRESENT THE MINIMUM ACCEPTABLE REQUIREMENTS, THEREFORE, WHERE DRAWINGS AND/OR SPECIFICATIONS INDICATE MATERIALS OR CONSTRUCTION IN EXCESS OF THESE CODE REQUIREMENTS, THE DRAWINGS AND/OR SPECIFICATIONS SHALL GOVERN.
- IT IS THE RESPONSIBILITY OF THE PLUMBING CONTRACTOR TO PAY FOR ALL NECESSARY PERMITS AND APPROVALS FOR THIS INSTALLATION.
- IT IS THE RESPONSIBILITY OF THE PLUMBING CONTRACTOR TO REVIEW THESE PLANS AND SPECIFICATIONS, AS WELL AS THE DOCUMENTS PREPARED BY THE ARCHITECT, ENGINEER, CONTRACTOR, SUBCONTRACTOR, INTEGRAL DECOR AND SITE ENGINEERING DRAWINGS TO BECOME FAMILIAR WITH THE FULL PROJECT SCOPE. IN ADDITION, THIS CONTRACTOR MUST COORDINATE WITH AN OWNER REPRESENTATIVE TO FULLY UNDERSTAND ALL REQUIREMENTS WHICH MAY NOT BE SPECIFIED HEREIN AND WHICH THE OWNER MAY CONSIDER PART OF THIS CONTRACT. DURING THE COURSE OF CONSTRUCTION COORDINATE AND ACTIVELY CONSTRUCTION, IT IS THE RESPONSIBILITY OF THE PLUMBING CONTRACTOR TO WORK CLOSELY WITH ALL ACCOMPANYING CONTRACTORS AND TRADESMEN IN ORDER TO ENSURE A SMOOTH RUNNING AND CAREFULLY COORDINATED INSTALLATION.
- ANY DISCREPANCIES OR INADEQUACIES WITHIN THESE BID DOCUMENTS OR BETWEEN THESE BID DOCUMENTS AND THE BID DOCUMENTS OF THE ARCHITECT, ENGINEER, CONTRACTOR, SUBCONTRACTOR, INTEGRAL DECOR AND SITE ENGINEERING DRAWINGS, OR BETWEEN THESE BID DOCUMENTS AND FIELD CONDITIONS MUST BE BROUGHT TO THE ATTENTION OF THE OWNER, ARCHITECT AND ENGINEER PRIOR TO BID SUBMISSION.
- THE PLUMBING CONTRACTOR SHALL VERIFY ALL EXISTING INVERT ELEVATIONS PRIOR TO BID SUBMISSION. IF ANY CONFLICTS EXIST BETWEEN THE NEW PLUMBING SYSTEMS AND THE EXISTING SITE LEVEL SYSTEMS, THEY SHOULD BE BROUGHT TO THE ATTENTION OF AN OWNER'S REPRESENTATIVE AND THE ENGINEER PRIOR TO BID SUBMISSION. EXTRA COMPENSATION WILL NOT BE GRANTED FOR ANY EXTRA WORK OR MATERIAL WHICH RESULTS FROM AN INABILITY TO MEET THE INVERTS OF THE EXISTING SITE LEVEL PIPING SYSTEMS.
- PLUMBING CONTRACTOR SHALL FURNISH AND INSTALL NEW PRODUCTS OF ESTABLISHED AND REPUTABLE MANUFACTURERS. DO NOT MAKE EQUIPMENT SUBSTITUTIONS THAT WOULD LEAVE INADEQUATE OPERATING OR SERVICE SPACE. PLUMBING CONTRACTOR SHALL INSTALL ALL EQUIPMENT IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDED INSTALLATION PROCEDURES AND IN AN ARRANGEMENT THAT WILL GIVE THE GREATEST PRACTICALITY AND CONVENIENCE TO THE OWNER. INSTALL MATERIALS AND EQUIPMENT SQUARELY WITH THE BUILDING LINES WHEREVER POSSIBLE.
- THE PLUMBING CONTRACTOR SHALL RUN ALL DOMESTIC WATER, WASTE, VENT AND GAS PIPING AS HIGH AS POSSIBLE THROUGHOUT THE ENTIRE BUILDING. INSTALL LONG RUNS OF PIPING WITHIN STEEL JOIST SPACE AND OTHER PIPING TIGHT TO BOTTOM OF STEEL. COORDINATE AND VERIFY WITH OTHER CONTRACTORS AS NOT TO INTERFERE WITH DUCTWORK, FIRE PROTECTION PIPING, LIGHTING SYSTEMS, ETC.
- ALL EXPOSED HORIZONTAL AND VERTICAL PIPING SHALL BE INSTALLED IN A NEAT ARRANGEMENT IN LOCATIONS WHICH ARE THE MOST INCONSPICUOUS. VERTICAL DROPS SHALL BE KEPT TO AN ABSOLUTE MINIMUM AND THEIR FINAL LOCATIONS SHALL BE COORDINATED AND RUN WITHIN CHASES, WALLS, SOFFITS WITH OTHER MECHANICAL/ELECTRICAL FEEDS. ALL SUCH LOCATIONS ARE TO BE REVIEWED WITH AN OWNER'S REPRESENTATIVE AND ARCHITECT PRIOR TO INSTALLATION.
- FINAL CONNECTIONS TO ALL GAS FIRED EQUIPMENT TO BE BY THE PLUMBING CONTRACTOR, REGARDLESS OF WHO PROVIDES EQUIPMENT. THIS SHALL INCLUDE BUT NOT BE LIMITED TO HVAC EQUIPMENT, WATER HEATERS, ETC. EACH PIECE OF EQUIPMENT SHALL BE PROVIDED WITH A DIRT LEG, LUBRICATED PLUG VALVE, UNION AND GAS SHUT-OFF VALVE.
- ALL PLUMBING FIXTURES / APPLIANCES SHALL HAVE THEIR OWN INDEPENDENT SHUT- OFF VALVES, INSTALLED IN AN EASILY ACCESSIBLE AND CONVENIENT LOCATION.
- ALL DOMESTIC WATER BRANCH LINES SHALL HAVE THEIR OWN RESPECTIVE SHUT-OFF VALVES WHETHER OR NOT SHOWN ON THE DRAWINGS.
- DOMESTIC WATER HEATER TEMPERATURE / PRESSURE RELIEF VALVES SHALL BE PIPED FULL SIZE TO THE NEAREST APPROVED STANDPIPE, FLOOR DRAIN OR SINK. THIS REQUIREMENT SHALL BE APPLICABLE TO ALL DOMESTIC WATER HEATING STORAGE VESSELS.

PLUMBING FIXTURE SCHEDULE

MARK	ITEM	DESCRIPTION	CONNECTIONS				MODEL
			COLD	HOT	WASTE	VENT	
WC-1	WATER CLOSET	FLOOR MOUNTED, VITREOUS WHITE CHINA WATER CLOSET WITH ELONGATED BOWL. PROVIDE Z6000AV-HET MANUAL 1.28 GPF FLUSH VALVE AND Z5955S-EL-STS WHITE TOILET SEAT.	1"	-	4"	2"	ZURN Z5655
WC-2	WATER CLOSET (ADA)	ADA HEIGHT FLOOR MOUNTED, VITREOUS WHITE CHINA WATER CLOSET WITH ELONGATED BOWL. PROVIDE Z6000AV-HET MANUAL 1.28 GPF FLUSH VALVE AND Z5955S-EL-STS WHITE TOILET SEAT.	1"	-	4"	2"	ZURN Z5665
UR-1	URINAL	TOP SPUD WHITE VITREOUS CHINA, Z6003AV-ULST 16 oz. pf MANUAL FLUSH VALVE, ZURN Z1221 URINAL CARRIER. REFER TO ARCHITECTURAL PLANS FOR INSTALLATION HEIGHT.	3/4"	-	2"	1-1/2"	ZURN Z5755-U
L-1	LAVATORY (ADA)	20" X 17" SELF RIMMING 4" CENTER SET LAVATORY. PROVIDE ZURN Z6650-XL METERING FAUCET, WILKINS ZW3870XL THERMOSTATIC MIXING VALVE, GRID STRAINER, ANGLE STOPS, P-TRAP AND PLUMBEREX MODEL 2003W UNDERSINK TRAP AND SUPPLY PROTECTION.	1/2"	1/2"	2"	1-1/2"	ZURN Z5114
L-2	LAVATORY (ADA)	19" X 17" WALL-HUNG 4" CENTER SET LAVATORY. PROVIDE ZURN Z6650-XL METERING FAUCET, WILKINS ZW3870XL THERMOSTATIC MIXING VALVE, GRID STRAINER, ANGLE STOPS, P-TRAP AND PLUMBEREX MODEL 2003W UNDERSINK TRAP AND SUPPLY PROTECTION.	1/2"	1/2"	2"	1-1/2"	ZURN Z5554
S-1	SINK	17.5 X 19" SINGLE BOWL DROP IN 18 GAUGE STAINLESS STEEL SINK WITH 3 HOLE 4" ON CENTER FAUCET LEDGE. PROVIDE JUST J-1174-KS FAUCET, BASKET STRAINER, ANGLE STOPS, AND P-TRAP.	1/2"	1/2"	2"	1-1/2"	JUST SLF-17519-A-GR
S-2	SINK	15" X 15" SINGLE BOWL DROP IN 18 GAUGE STAINLESS STEEL SINK WITH 3 HOLE 4" ON CENTER FAUCET LEDGE. PROVIDE JUST J-1174-KS FAUCET, BASKET STRAINER, ANGLE STOPS, AND P-TRAP.	1/2"	1/2"	2"	1-1/2"	JUST SLF-1515-A-GR
WCO	WALL CLEANOUT	WALL CLEANOUT, DURA-COATED CAST IRON BODY, GAS AND WATERTIGHT ABS TAPERED THREAD PLUG, AND ROUND, SMOOTH STAINLESS STEEL ACCESS COVER WITH SECURING SCREW.	-	-	2"	-	ZURN Z1441

PIPING MATERIAL SCHEDULE

SERVICE	SIZE	PIPE MATERIAL	JOINTS	FITTINGS	NOTES
DOMESTIC COLD AND HOT WATER (BELOW GRADE)	ALL	SOFT DRAWN TYPE K COPPER TUBING OR APPROVED EQUAL	LEAD FREE SOLDER	WROUGHT COPPER	PROTECT PIPING UNDER PENETRATING CONCRETE WITH POLYETHYLENE SLEEVES, NO FITTINGS UNDER CONCRETE.
DOMESTIC COLD AND HOT WATER (ABOVE GRADE)	ALL	HARD DRAWN TYPE L COPPER PIPE OR APPROVED EQUAL	LEAD FREE SOLDER	WROUGHT COPPER	
SANITARY WASTE AND VENT - WHERE ALLOWED	ALL	SCH. 40 PVC OR ABS OR APPROVED EQUAL	SOLVENT WELD	MATCH PIPE	ASTM D-2661-78 ASTM D-2664-80 ASTM D-2665-82
SANITARY WASTE AND VENT - WHERE REQUIRED	ALL	CAST IRON	NO-HUB	MATCH PIPE	DOMESTIC MANUFACTURED CAST IRON PRODUCTS ONLY.

SEE SPECIFICATIONS FOR ADDITIONAL INFORMATION.


PLUMBING LEGEND

SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
CD	CONDENSATE DRAIN	—	BALL VALVE
—	DOMESTIC COLD WATER	—	BUTTERFLY VALVE
—	DOMESTIC HOT WATER	—	GAS SHUT OFF VALVE
—	DOMESTIC HOT WATER RETURN	—	ANGLE VALVE
—	DOMESTIC HOT WATER (140° F)	—	GLOBE VALVE
—	DOMESTIC HOT WATER RETURN (140° F)	—	MOTORIZED T.C. VALVE 2-WAY
RCW	RAW COLD WATER	—	MOTORIZED T.C. VALVE 3-WAY
F	FIRE PROTECTION	—	PRESSURE REDUCING VALVE
—	WASTE ABOVE GROUND	—	SAFETY RELIEF VALVE
—	WASTE BELOW GROUND	—	GATE VALVE
—	VENT	—	SHUT-OFF VALVE IN RISER
—	GREASE WASTE	—	SWING CHECK VALVE
—	ACID WASTE ABOVE GROUND	—	BACKFLOW PREVENTER
—	ACID WASTE BELOW GROUND	—	MANUAL FLOW BALANCING VALVE (CIRCUIT SETTER)
—	ACID VENT	—	DIAL THERMOMETER
RDL	ROOF DRAIN LEADER	—	PRESSURE GAUGE W/ SNUBBER
ODL	OVERFLOW DRAIN LEADER	—	STRAINER
G	NATURAL GAS	—	FLEX CONNECTOR
LPG	LIQUEFIED PETROLEUM GAS (PROPANE)	—	UNION
MPG	MEDIUM PRESSURE NATURAL GAS	—	TEE UP
HPG	HIGH PRESSURE NATURAL GAS	—	TEE DOWN
A	COMPRESSED AIR	—	ELBOW UP
V	VACUUM	—	ELBOW DOWN
N	MEDICAL NITROGEN	—	WATER METER
N2O	MEDICAL NITROUS OXIDE	—	GAS METER
CO2	CARBON DIOXIDE	—	WATER HAMMER ARRESTOR (WHA)
(E)	EXISTING PIPING	—	HOSE BIBB, EXPOSED
—	DEMOLITION WORK	—	HOSE BIBB, RECESSED
S = -	SLOPE DOWN IN DIRECTION OF FLOW	—	AUTOMATIC AIR VENT
UNI	EQUIPMENT TAG	—	CONNECT NEW WORK TO EXISTING
DIAGRAM SHEET	DIAGRAM TAG CALLOUT	—	FLOW INDICATOR
DIAGRAM	DIAGRAM TAG	—	PIPE CAP
—	—	—	IN-LINE CIRCULATION PUMP
—	—	—	TRAP PRIMER
—	—	—	PIPE BREAK
—	—	—	SUMP PUMP
ΦΦ	—	—	TWO WAY GRADE CLEAN OUT
Φ	—	—	FLOOR CLEAN OUT / CLEAN OUT TO GRADE
-P	—	—	WALL CLEAN OUT
II	—	—	FLOOR DRAIN
II	—	—	FLOOR SINK
—	—	—	ROOF / OVERFLOW DRAIN

NOTE: NOT ALL SYMBOLS MAY BE USED

SHEET INDEX

SHEET NUMBER	SHEET TITLE	100% CD M4-2016
P0.01	GENERAL INFORMATION AND SCHEDULES	●
P0.02	PLUMBING DEMO FLOOR PLAN	●
P1.01	PLUMBING FLOOR PLAN	●



REVISIONS:

KGA ARCHITECTURE
1701 Directon Boulevard, Suite 770
Austin, Texas 78744
512.441.8200

LAS VEGAS
907 West Diablo Drive, Third Floor
Las Vegas, Nevada 89148
702.367.6900

PROJECT:
UNLV MARYLAND
ADMINISTRATIVE BUILDING
TENANT IMPROVEMENT


CONSULTANTS:
MECHANICAL / PLUMBING / ELECTRICAL
TJK CONSULTING ENGINEERS, INC.
PHONE 070 871-3621

DATE:
APRIL 25, 2016

JOB NO:
16323.00

Sheet:

P0.01




GENERAL NOTES:

1. PLUMBING CONTRACTOR SHALL FIELD VERIFY ALL EXISTING CONDITIONS PRIOR TO START.
2. COORDINATE ALL PLUMBING WORK FOR POTENTIAL CONFLICTS WITH OTHER TRADES.
3. UNLESS OTHERWISE NOTED ALL PLUMBING EQUIPMENT SHALL REMAIN.

UNLV

MARYLAND ADMINISTRATIVE BUILDING I

TENANT IMPROVEMENT



KEY NOTES:

1. REMOVE EXISTING WATER CLOSETS AND LAVATORIES IN THIS RESTROOM. PREPARE WASTE, VENT AND WATER PIPING FOR NEW FIXTURES TO BE INSTALLED.
2. REMOVE EXISTING WATER CLOSETS, URINALS AND LAVATORIES IN THIS RESTROOM. PREPARE WASTE, VENT AND WATER PIPING FOR NEW FIXTURES TO BE INSTALLED.
3. REMOVE EXISTING SINK. PREPARE WASTE, VENT AND WATER PIPING FOR NEW FIXTURES TO BE INSTALLED.
4. REMOVE EXISTING FIXTURE. REMOVE WATER PIPING BACK TO MAIN AND CAP. CUT WASTE PIPE BACK TO BELOW GRADE AND CAP. REMOVE VENT PIPING BACK TO MAIN AND CAP.

KGA ARCHITECTURE
 1701 Directon Boulevard, Suite 770
 Austin, Texas 78744
 512.441.8200
 www.KGArchitects.com

CONSULTANTS:
 MECHANICAL / PLUMBING / ELECTRICAL
TJK CONSULTING ENGINEERS, INC.
 PHONE 702.871.3621

PROJECT:
UNLV MARYLAND
ADMINISTRATIVE BUILDING I
TENANT IMPROVEMENT

Sheet Contents:
PLUMBING DEMO FLOOR
PLAN

JK
 tjk consulting engineers, inc.
 5459 S. Durango Dr., Suite 100
 Las Vegas, NV 89113
 P: 702.871.3621
 F: 702.871.8353
 www.tjkengineering.com
 JK # 15122

DATE: APRIL 25, 2016
JOB NO.: 16323.00
Sheet:

P0.02

UNLV
MARYLAND ADMINISTRATIVE BUILDING I
TENANT IMPROVEMENT

KGA ARCHITECTURE
1701 Director Boulevard, Suite 770
Austin, Texas 78744
512.441.8200
www.kgarchitects.com


CONSULTANTS:
MECHANICAL / PLUMBING / ELECTRICAL
TJK CONSULTING ENGINEERS, INC.
PHONE 702.871.8321
www.tjkengineers.com

PROJECT:
UNLV MARYLAND
ADMINISTRATIVE BUILDING I
TENANT IMPROVEMENT

Sheet Contents:
PLUMBING FLOOR PLAN

DATE: APRIL 25, 2016
Job No.: 16323.00
Sheet:

P1.01



GENERAL NOTES:

1. ALL PLUMBING FIXTURES SHALL BE WATER CONSERVATION TYPE AS MANDATED BY LOCAL BLDG. DEPT.
2. PRIOR TO DETAILING & INSTALLING PLUMBING AND FIRE PROTECTION PIPING, COORDINATE EXACT ROUTING AND ELEVATION WITH MECHANICAL, ELECTRICAL, AND FIRE SPRINKLER CONTRACTORS. PROVIDE WRITTEN CONFIRMATION THAT THIS COORDINATION HAS BEEN IMPLEMENTED PRIOR TO PROCEEDING WITH INSTALLATION OF PIPING.
3. ALL PLUMBING FIXTURES SHALL HAVE A TRAP INSTALLED AND SHALL BE PROPERLY VENTED IN ORDER TO MAINTAIN THE TRAP SEAL.

REVISIONS:

KEY NOTES:

1. PROVIDE AND INSTALL NEW FIXTURE(S).
2. PROVIDE AND INSTALL NEW FIXTURE. EXTEND ROUGH-INS OF NEW FIXTURES TO EXISTING POINTS OF CONNECTION.

UNLV
MARYLAND ADMINISTRATIVE BUILDING I
TENANT IMPROVEMENT

KGA ARCHITECTURE
1701 Director Boulevard, Third Floor
Austin, Texas 78744
512.441.8200
www.kgarchitects.com


CONSULTANTS:
MECHANICAL / PLUMBING / ELECTRICAL
TJK CONSULTING ENGINEERS, INC.
PHONE 702.871.8321
www.tjkengineers.com

PROJECT:
UNLV MARYLAND
ADMINISTRATIVE BUILDING I
TENANT IMPROVEMENT

Sheet Contents:
PLUMBING FLOOR PLAN

DATE: APRIL 25, 2016
Job No.: 16323.00
Sheet:

P1.01



REVISIONS:

- IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO LOOK THROUGH ALL DRAWINGS ASSOCIATED WITH THIS PROJECT, WORK ASSOCIATED WITH THE ELECTRICAL CONTRACTOR'S TRADE MAY BE SHOWN ON OTHER DRAWINGS, AND ADDITIONAL COST RESULTING FROM THE FAILURE TO INCLUDE THESE ITEMS SHOWN ON THE OTHER DRAWINGS WILL BE INCURRED BY CONTRACTOR.
- IT IS THE INTENT OF THESE DRAWINGS AND SPECIFICATIONS TO ESTABLISH A STANDARD OF QUALITY. THE ENGINEER RESERVES THE RIGHT TO ALLOW OTHER METHODS AND MATERIALS NOT REFLECTED HEREIN. THE CONTRACTOR IS RESPONSIBLE TO REQUEST THE ENGINEER WAIVE THE STANDARDS TO ALLOW ALTERNATE METHODS AND MATERIALS. PRIOR TO BEGINNING THE PROJECT, CONTRACT DOCUMENTS REVISES TO ACCOMMODATE INSTALLED CONDITIONS, WITHOUT PRIOR APPROVAL, WILL RESULT IN ADDITIONAL DESIGN CHARGES TO THE CONTRACTOR.
- ELECTRICAL WORK SHALL BE PERFORMED IN A WORKMANLIKE MANNER IN ACCORDANCE WITH THE NECA INSTALLATION STANDARDS TO THE SATISFACTION OF THE ARCHITECT AND ENGINEER.
- ALL WORK, MATERIALS AND EQUIPMENT SHALL CONFORM TO THE CURRENTLY ADOPTED EDITION OF ALL APPLICABLE NATIONAL, STATE AND CITY CODES AND ORDINANCES.
- ALL ELECTRICAL SYSTEM COMPONENTS SHALL BE LISTED OR LABELED BY UL OR OTHER RECOGNIZED TESTING FACILITY AS ALLOWED BY AUTHORITY HAVING JURISDICTION.
- WHERE AN APPARENT DISCREPANCY EXISTS BETWEEN THE REQUIREMENTS OF THE GENERAL NOTES AND INFORMATION PORTRAYED IN THE ELECTRICAL DRAWINGS, THE CONTRACTOR SHALL INCLUDE IN THE BID THE COST OF THE GREATER QUALITY OR QUANTITY.
- CONTRACTOR SHALL VISIT JOB SITE PRIOR TO BID AND VERIFY EXISTING CONDITIONS.
- CONTRACTOR SHALL INCLUDE IN BASE BID ALL COSTS REQUIRED FOR PERMITS AND INSPECTIONS.
- CONTRACTOR SHALL VERIFY, WITH OWNER'S REPRESENTATIVE PRIOR TO SUBMITTING BID, ALLOWABLE WORKING HOURS, EMPLOYEE PARKING AREA, MATERIAL DELIVERY, STORAGE REQUIREMENTS, DEMOLITION AND DEMOLITION METHODS AS WELL AS ALL OTHER BID REQUIREMENTS. INCLUDE ALL COSTS IN BID FOR DUST BARRIERS, DUMPSTERS ETC. AS REQUIRED FOR THE DURATION OF THE PROJECT. PERFORM ALL WORK AS DIRECTED BY OWNER'S REPRESENTATIVE AND ARCHITECT.
- ALL ELECTRICAL SYSTEMS SHALL BE TESTED FOR PROPER OPERATION. IF TESTS SHOW THAT WORK IS DEFECTIVE, CONTRACTOR SHALL MAKE ALL NECESSARY CORRECTIONS AT NO ADDITIONAL COST TO OWNER.
- CONTRACTOR SHALL GUARANTEE ALL WORK AGAINST DEFECTS IN MATERIALS AND WORKMANSHIP WHICH MAY OCCUR UNDER NORMAL USE FOR A PERIOD OF ONE YEAR AFTER OWNER'S ACCEPTANCE. ALL DEFECTS SHALL BE PROMPTLY CORRECTED BY CONTRACTOR WITHOUT ADDITIONAL COST TO OWNER.
- PROVIDE AS-BUILT DRAWINGS TO ARCHITECT. DRAWINGS SHALL INCLUDE ACCURATE CONDUIT AND DEVICE LOCATIONS DIMENSIONED FROM PERMANENT LANDMARKS SUCH AS BUILDING WALLS.
- DO NOT SCALE ELECTRICAL DRAWINGS. VERIFY EXACT LOCATION OF ALL DEVICES, JUNCTION BOXES, LIGHTING FIXTURES, ETC. WITH ARCHITECTURAL AND INTERIOR DESIGN DRAWINGS PRIOR TO INSTALLATION. CONTRACTOR SHALL VERIFY THE EXACT LOCATION OF ALL MECHANICAL EQUIPMENT AND OTHER EQUIPMENT REQUIRING ELECTRICAL CONNECTION PRIOR TO ROUGH-IN. EVERY OUTLET HEIGHT SHALL BE VERIFIED ON EACH WALL WITH THE INTERIOR PLANNING AND DESIGN DRAWINGS. COORDINATE WITH CABINET SHOP DRAWINGS TO ENSURE PROPER HEIGHT AND LOCATION WITH RESPECT TO MILLWORK, EQUIPMENT, ETC.
- THESE DRAWINGS INDICATE THE FINISHED REQUIREMENTS FOR THE ELECTRICAL SYSTEM. EQUIPMENT, LIGHTING FIXTURES, OUTLETS AND DEVICES, DUE TO STRUCTURAL CONDITIONS, MECHANICAL DUCT, PIPING CONDUITS, OR OTHER LEVERAGE REASONS, THE CONTRACTOR MAY DESIRE TO INSTALL THE WORK IN A MANNER DIFFERENT FROM THAT DRAWN. SUCH WORK SHALL BE APPROVED BY THE OWNER'S REPRESENTATIVE FOR REVIEW AND APPROVAL PRIOR TO PROCEEDING. UPON APPROVAL, THE WORK SHALL BE PERFORMED AND THE AS-BUILT DRAWINGS SHALL BE REVISED TO ACCURATELY REFLECT THE WORK AS ACTUALLY INSTALLED.
- ANY VARIANCE OR EXCEPTIONS THE THE DRAWINGS AND SPECIFICATIONS MUST BE REQUESTED AND APPROVED IN WRITING BY THE ENGINEER. WHERE UNAUTHORIZED CHANGES ARE FOUND, THE CONTRACTOR SHALL REMOVE THE INSTALLED WORK AND INSTALL ITS AS SHOWN ON THE DRAWINGS AT NO ADDITIONAL COST THAT THE OWNER COST SHALL INCLUDE ANY CUTTING, PATCHING, PAINTING AND REPAIR COST TO INSTALLED CEILINGS, WALLS ETC AS REQUIRED FOR CORRECTING THE DEFICIENCY.
- RACEWAY SYSTEMS ARE SHOWN DIAGRAMMATICALLY. ACTUAL LOCATION AND ROUTING OF ALL, SHALL BE DETERMINED BY CONTRACTOR TO SUIT FIELD CONDITIONS.
- RACEWAYS SHALL BE INSTALLED CONCEALED WHENEVER POSSIBLE. RACEWAYS INSTALLED EXPOSED (AS APPROVED BY ENGINEER IN WRITING PRIOR TO ROUGH-IN) SHALL BE ROUTED OUT OF PUBLIC VIEW AS MUCH AS POSSIBLE. RACEWAYS SHALL BE RUN PARALLEL WITH, OR AT RIGHT ANGLE TO WALLS.
- PROVIDE UL APPROVED EXPANSION FITTINGS WHERE RACEWAYS CROSS EXPANSION JOINTS. PROVIDE DIAULIC THERMALLY SIZED PERMITS WHERE REQUIRED. PROVIDE ALL FIXTURES AND FITTINGS FOR A COMPLETE INSTALLATION. REFER TO ARCHITECTURAL DRAWINGS FOR EXPANSION JOINT LOCATION(S).
- CONTRACTOR SHALL PROVIDE ALL RACEWAY SYSTEMS INDICATED ON THE DRAWINGS. NO REQUIREMENT FOR ANOTHER. NOTES ANY DEFLECTION FROM WIRING METHODS INDICATED SHALL BE ALLOWED ONLY BY SPECIFIC WRITTEN APPROVAL FROM EITHER THE ARCHITECT, ENGINEER OR OWNER. CONTRACTOR'S BID SHALL INCLUDE ALL COSTS FOR RACEWAY SYSTEMS AS SPECIFIED UNLESS SPECIFIC WRITTEN APPROVAL FOR AN ALTERNATIVE WIRING METHOD IS OBTAINED FROM EITHER THE ARCHITECT, ENGINEER OR OWNER AND IS SUBMITTED AS PART OF CONTRACTOR'S FORMAL BID PROPOSAL.
- PRIOR TO INSTALLATION, CONTRACTOR SHALL REVIEW THE COMPLETE SET OF CONSTRUCTION DOCUMENTS FOR CONFLICTS WITH OTHER TRADES. CONTRACTOR SHALL BE RESPONSIBLE TO COORDINATE ALL WORK WITH OTHER TRADES TO AVOID CONFLICT DURING INSTALLATION. CONTRACTOR SHALL MAKE MINOR ADJUSTMENTS IN EQUIPMENT LOCATION AND ROUTING AS NECESSARY AT NO ADDITIONAL COST TO THE OWNER.
- CONTRACTOR SHALL BE RESPONSIBLE TO PROPERLY CUT AND PATCH EXISTING CONSTRUCTION AS REQUIRED TO INSTALL NEW ELECTRICAL WORK. ALL PATCHING SHALL BE OF THE SAME MATERIALS, WORKMANSHIP AND FINISH AS EXISTING WORK AND SHALL ACCURATELY MATCH ALL SURROUNDING WORK TO THE SATISFACTION OF THE ARCHITECT.
- ALL ELECTRICAL EQUIPMENT SHALL HAVE SUFFICIENT GUTTER SPACE AND LUGS TO ACCOMMODATE QUANTITY AND SIZE OF CONDUCTORS REQUIRED. CONTRACTORS SHALL PROVIDE EQUIPMENT WITH OVERSIZED ENCLOSURES WHERE REQUIRED.
- COORDINATE ELECTRICAL REQUIREMENTS FOR ALL PLUMBING AND MECHANICAL EQUIPMENT WITH FINAL CONTRACTOR SELECTION. THE CONTRACTOR SHALL SIZE DISCONNECTS BASED UPON CIRCUIT BREAKER RATINGS AND PROVIDE FUSING AS REQUIRED PER EQUIPMENT MANUFACTURER RECOMMENDATIONS AND UL LISTING REQUIREMENT
- SIZING OF MOTOR-RELATED ELECTRICAL COMPONENTS, INCLUDING FEEDER AND/OR BRANCH CIRCUITS (WIRE AND CONDUIT) AND OVERCURRENT PROTECTION (BREAKER AND/OR FUSES) IS BASED ON RATINGS INDICATED. THE CONTRACTOR EQUIPMENT IS AS SHOWN AS NEC APPROXIMATED TO SIZE FOR A GIVEN MOTOR AND POWER SOURCE, STATION AND PHASE. IT IS THE CONTRACTOR'S RESPONSIBILITY TO DETERMINE MOTOR AND APPLIANCE RATINGS AND LOADS. CONTRACTOR TO PROVIDE CORRECTLY SIZED MOTOR OVERLOAD ELECTRICAL COMPONENTS BASED ON NAMEPLATE RATING. REFLECT ALL CHANGES IN THE AS-BUILT DRAWINGS.
- THE ELECTRICAL CONTRACTOR PRIOR TO ROUGH-IN, SHALL VERIFY ALL HV/AC AMPERAGES, PHASES AND VOLTAGES AGAINST PLAN REQUIREMENTS AND NOTIFY ENGINEER/ARCHITECT OF ANY DISCREPANCIES. FAILURE TO VERIFY AND NOTIFY ENGINEER/ARCHITECT PRIOR TO ROUGH-IN, SHALL RESULT IN THE ELECTRICAL CONTRACTOR ASSUMING RESPONSIBILITY FOR DESIGN AND INSTALLATION REQUIREMENTS.
- THE ELECTRICAL CONTRACTOR SHALL INSURE FINAL COORDINATION OF THE MANUFACTURERS RECOMMENDED FUSE SIZES FOR THE INSTALLED MECHANICAL EQUIPMENT WITH THE SIZE DISCONNECT PRIOR TO OR DURING ROUGH-IN. ADVISE ENGINEER IF CHANGES IN THE FINAL SELECTION OF MECHANICAL EQUIPMENT HAVE IMPACTED DISCONNECT SWITCH, BREAKER, OR CONDUCTOR SIZES.
- CONTRACTOR SHALL ENGAGE THE SERVICES FOR A STATE LICENSED FIRE ALARM MANUFACTURER/INSTALLER TO PREPARE ALL DESIGN DRAWINGS AND CALCULATIONS REQUIRED FOR SYSTEM APPROVAL BY THE AUTHORITY HAVING JURISDICTION. SUBMIT ALL PLANS AND PROVIDE ALL PERMITS REQUIRED FOR A COMPLETE AND OPERABLE APPROVED LIFE SAFETY SYSTEM.
- ALL PENETRATIONS OF FIRE RESISTIVE FLOORS OR WALLS SHALL BE PROTECTED BY MATERIALS AND INSTALLATION DIAGRAMS THAT CONFORM TO UL LISTING FOR "THROUGH-PENETRATION FIRE STOP SYSTEMS".
- WHERE MOTORS ARE INSTALLED IN SUSPENDED CEILINGS, CONTRACTOR SHALL PROVIDE DISCONNECT SWITCH IN SUSPENDED CEILING WITHIN REACH FROM ACCESS POINT.
- VERIFY DEVICE COLOR AND MOUNTING ORIENTATION (VERTICAL OR HORIZONTAL) WITH ARCHITECTURAL AND INTERIOR DESIGN DRAWINGS PRIOR TO ORDERING ANY EQUIPMENT AND PROVIDE DEVICES AS REQUIRED. UNLESS NOTED OTHERWISE, DEVICES AND DEVICE PLATES SHALL BE WHITE IN COLOR.

ELECTRICAL LEGEND

NOTE: NOT ALL SYMBOLS CONTAINED HEREIN MAY APPEAR IN THESE DRAWINGS.


EXT	DEMO	NEW	DEFINITION	EXT	DEMO	NEW	DEFINITION
—	—	—	PANELBOARD SURFACE MOUNTED	(M)	(M)	(M)	METERING
—	—	—	PANELBOARD FLUSH MOUNTED	(KWH)	(KWH)	(KWH)	KILOWATT HOUR DEMAND METER
TC	TC	TC	SWITCHBOARD	(D)	(D)	(D)	
T	T	T	TERMINAL CABINET	(W)	(W)	(W)	TRANSFORMER
P	P	P	PULLBOX	(O)	(O)	(O)	MOTOR OUTLET
□	□	□	MOTOR STARTER	(G)	(G)	(G)	GENERATOR
□	□	□	COMBINATION MOTOR STARTER	(S)	(S)	(S)	GROUND ROD
□	□	□	COMBINATION MOTOR STARTER VENDOR FURNISHED	(SV)	(SV)	(SV)	SOLENOID VALVE
□	□	□	DISCONNECT SWITCH "F" INDICATES FUSIBLE	(S)	(S)	(S)	SPEAKER
□	□	□	DISCONNECT SWITCH VENDOR FURNISHED	(M)	(M)	(M)	MOTION DETECTOR
TTS	TTS	TTS	CONTACTOR	(TV)	(TV)	(TV)	CCTV SURVEILLANCE CAMERA OUTLET
TTC	TTC	TTC	CONTACTOR VENDOR FURNISHED	(TV)	(TV)	(TV)	TELEVISION ANTENNA OUTLET
A	A	A	TELEPHONE TERMINAL BOARD 4 X 8 X 3/4" FIRE TREATED PLYWOOD	(P)	(P)	(P)	PULL STATION
A	A	A	FLUORESCENT FIXTURE - LETTER DENOTES TYPE	(HORN)	(HORN)	(HORN)	FLOW SWITCH
A	A	A	WALL MOUNTED FIXTURE (FLUORESCENT SHOWN) - LETTER DENOTES TYPE	(HORN)	(HORN)	(HORN)	TAMPER SWITCH
A	A	A	HID OR INCANDESCENT FIXTURE - LETTER DENOTES TYPE	(S)	(S)	(S)	STROBE
A	A	A	FLUORESCENT STRIP FIXTURE - LETTER DENOTES TYPE	(FACP)	(FACP)	(FACP)	FIRE ALARM CONTROL PANEL
A	A	A	TRACK LIGHTING - LETTER DENOTES TYPE	(FAA)	(FAA)	(FAA)	FIRE ALARM ANNUNCIATOR
A	A	A	EMERGENCY LIGHTING UNIT - LETTER DENOTES TYPE	(DH)	(DH)	(DH)	DOOR HOLDER
A	A	A	EXIT FIXTURE - SHADED AREA DENOTES LIGHTED FACE, ARROWS DENOTE DIRECTION - LETTER DENOTES TYPE	(S)	(S)	(S)	SMOKE DETECTOR LETTER (X) INDICATES TYPE
A	A	A	EMERGENCY OR NIGHT LIGHT CONNECTED FIXTURE (FLUORESCENT SHOWN) - LETTER DENOTES TYPE	(H)	(H)	(H)	HEAT DETECTOR LETTER (X) INDICATES TYPE
A	A	A	POLE MOUNTED HID AREA LIGHT - LETTER DENOTES TYPE	(R)	(R)	(R)	R RATE OF RISE
A	A	A	SPORTS FIELD POLE ASSEMBLY	(F)	(F)	(F)	F FIXED TEMPERATURE
A	A	A	SINGLE RECEPTACLE 18" AFF UNLESS NOTED OTHERWISE	(SD)	(SD)	(SD)	FIREMAN PHONE
A	A	A	DUPLEX RECEPTACLE 18" AFF UNLESS NOTED OTHERWISE	(FS)	(FS)	(FS)	SMOKE/FIRE DAMPER
A	A	A	FLOOR MOUNTED DUPLEX RECEPTACLE	(T)	(T)	(T)	CONTROL DEVICE LETTERS INDICATE TYPE: FLS = FLOOR SWITCH, PLS = PILOT SWITCH, TPS = LIMIT SWITCH, PES = PNEUMATIC SWITCH, PS = PRESSURE SWITCH, TS = TEMPERATURE SWITCH
A	A	A	QUADRUPLE RECEPTACLE 18" AFF UNO	(A)	(A)	(A)	JUNCTION BOX (USED FOR CLARITY ONLY)
A	A	A	ISOLATED GROUND TYPE (ORANGE) DUPLEX RECEPTACLE AT 18" AFF UNO	(AS)	(AS)	(AS)	AMMETER
A	A	A	ISOLATED GROUND TYPE (ORANGE) QUADRUPLE RECEPTACLE AT 18" AFF UNO	(V)	(V)	(V)	AMMETER SWITCH
A	A	A	COUNTER HEIGHT RECEPTACLE (VERIFY HEIGHT)	(VS)	(VS)	(VS)	VOLTMETER
A	A	A	GFI DUPLEX RECEPTACLE 18" AFF UNLESS NOTED OTHERWISE	(B)	(B)	(B)	VOLTMETER SWITCH
A	A	A	SWITCHED DUPLEX RECEPTACLE 18" AFF UNLESS NOTED OTHERWISE	(ST)	(ST)	(ST)	RELAY OR CONTROL DEVICE. NUMBER REPRESENTS STANDARD DEVICE
A	A	A	ELECTRIC SHEET NOTE DESIGNATION	(GFI)	(GFI)	(GFI)	SHUNT TRIP
A	A	A	MECHANICAL EQUIPMENT CROSS REFERENCE	(GFI)	(GFI)	(GFI)	GROUND FAULT INTERRUPTER
A	A	A	SPECIAL PURPOSE RECEPTACLE - NUMBER REFERS TO RECEPTACLE SCHEDULE	(CLOCK)	(CLOCK)	(CLOCK)	
A	A	A	CLOCK OUTLET	(24)	(24)	(24)	
A	A	A	MULTIOUTLET ASSEMBLY - ARROW HEADS INDICATE EXTENT, NUMBERS INDICATE SPACING IN INCHES	(S)	(S)	(S)	
A	A	A	SINGLE POLE SWITCH 48" AFF UNO	(S)	(S)	(S)	
A	A	A	THREE WAY SWITCH 48" AFF UNO	(S)	(S)	(S)	
A	A	A	FOUR WAY SWITCH 48" AFF UNO	(S)	(S)	(S)	
A	A	A	KEY OPERATED SWITCH	(D)	(D)	(D)	
A	A	A	DIMMER OPERATED SWITCH	(S)	(S)	(S)	
A	A	A	SWITCH WITH PILOT LIGHT	(S)	(S)	(S)	
A	A	A	MOTION SENSING SWITCH	(S)	(S)	(S)	
A	A	A	CONTROL STATION	(S)	(S)	(S)	
A	A	A	TELEPHONE OUTLET 18" AFF UNO	(S)	(S)	(S)	
A	A	A	PAY TELEPHONE OUTLET 48" AFF UNO	(S)	(S)	(S)	
A	A	A	FLOOR MOUNTED TELEPHONE OUTLET	(S)	(S)	(S)	
A	A	A	COMPUTER OUTLET OR SPECIAL PURPOSE COMMUNICATIONS	(S)	(S)	(S)	
A	A	A	ROUTER OUTLET	(S)	(S)	(S)	
A	A	A	PHOTOELECTRIC CELL	(TC)	(TC)	(TC)	
A	A	A	TIME CLOCK	(TC)	(TC)	(TC)	
A	A	A	BRANCH CIRCUIT CONSISTING OF 2x12 IN MINIMUM SIZE CONDUIT NOT INCLUDING GROUND WIRE	(TC)	(TC)	(TC)	
A	A	A	HOME RUN TO PANELBOARD OR DEVICE - NUMBER OF ARROW HEADS INDICATES NUMBER OF CIRCUITS	(BKR)	(BKR)	(BKR)	
A	A	A	BRANCH CIRCUIT - SHORT SLASHES INDICATE NUMBER OF PHASE CONDUCTORS, LONG SLASH W/ A DOT INDICATES NUMBER OF NEUTRALS, LONG SLASH W/ A DOT INDICATES A SEPARATE ISOLATED GROUND WIRE	(C)	(C)	(C)	
A	A	A	CONDUIT IN SLAB OR UNDERGROUND	(C.O.)	(C.O.)	(C.O.)	
A	A	A	CONDUIT SEALING FITTING (USED FOR CLARITY ONLY)	(DWG)	(DWG)	(DWG)	
A	A	A	INTERRUPTER SWITCH	(ELEC)	(ELEC)	(ELEC)	
A	A	A	CIRCUIT BREAKER	(EXT)	(EXT)	(EXT)	
A	A	A	DRAWOUT CIRCUIT BREAKER	(GFI)	(GFI)	(GFI)	
A	A	A	GROUND	(GND)	(GND)	(GND)	

ABBREVIATIONS:

AFF	ABOVE FINISHED FLOOR	J-BOX	JUNCTION BOX
AFG	ABOVE FINISHED GRADE	KVA	KILOWATT AMPS
AL	ALUMINUM	KW	KILOWATT
BKR	BREAKER	LTG	LIGHTING
C	CONDUIT	NTS	NOT TO SCALE
CKT	CIRCUIT	PNL	PANEL
C.O.	CONDUIT ONLY	PWR	POWER
CU	COPPER	TYP	Typical
DWG	DRAWING	UNO	UNLESS NOTED OTHERWISE
ELEC	ELECTRICAL	V	VOLTS
EXT	EXISTING	VA	VOLT AMPS
GFI	GROUND FAULT INTERRUPT	WP	WEATHER PROOF
GND	GROUND	XFMR	TRANSFORMER

SHEET INDEX

SHEET NUMBER	SHEET TITLE
--------------	-------------



REVISIONS

Section # & Req.ID	Rough-In Electrical Inspection	Complies?	Comments/Assumptions
C405.2.2. [EL22] ¹	Automatic controls to shut off all building lighting installed in all buildings.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Requirement will be met.
C405.2.1. [EL13] ¹	Indirect lighting controls installed in any lighting plans and all manual controls readily accessible and visible to occupants.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Requirement will be met.
C405.2.1. [EL15] ¹	Lighting controls installed to uniformly reduce the lighting load by at least 50%.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Requirement will be met.
C405.2.2. [EL16] ¹	Daylight zones provided with individual controls that control the lights independent of general area lighting.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Exception: Requirement does not apply.
C405.2.3 [EL17] ¹	Sleeping units have at least one master switch at the main entry door that controls wired luminaires and switched receptacles.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Exception: Requirement does not apply.
C405.2.2. [EL18] ¹	Occupancy sensors installed in required spaces.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Requirement will be met.
C405.2.2. [EL20] ¹	Primary sidelighted areas are equipped with required lighting controls.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Exception: Requirement does not apply.
C405.2.2. [EL21] ¹	Enclosed spaces with daylight areas under skylights and rooftop monitors are equipped with required lighting controls.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Exception: Requirement does not apply.
C405.2.3 [EL4] ¹	Separate lighting control devices for specific uses installed per approved lighting plans.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Requirement will be met.
C405.3 [EL19] ¹	Fluorescent luminaires with odd numbered lamp configurations that are with 10 feet center to center (residential) or 12 feet center to edge to edge (if pendant or surface mounted) shall be tandem wired.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Exception: Requirement does not apply.
C405.4 [EL6] ¹	Exit signs do not exceed 5 watts per face.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Requirement will be met.
C405.2.3 [EL8] ¹	Additional interior lighting power allowed for special functions per the approved lighting plans and is automatically controlled and separated from general lighting.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Requirement will be met.

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: UNLV MOB Report date: 03/16/16
Data filename: J:\2015\15122 UNLV Maryland Office Building #1 MOB 1\OFFICE\ CALC LTG\IECC\20160316-151 Page 4 of 6
ELECTRICAL.IECC.cck

Section # & Req.ID	Rough-In Electrical Inspection	Complies?	Comments/Assumptions
C405.2.2. [EL22] ¹	Automatic controls to shut off all building lighting installed in all buildings.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Requirement will be met.
C405.2.1. [EL13] ¹	Indirect lighting controls installed in any lighting plans and all manual controls readily accessible and visible to occupants.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Requirement will be met.
C405.2.1. [EL15] ¹	Lighting controls installed to uniformly reduce the lighting load by at least 50%.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Requirement will be met.
C405.2.2. [EL16] ¹	Daylight zones provided with individual controls that control the lights independent of general area lighting.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Exception: Requirement does not apply.
C405.2.3 [EL17] ¹	Sleeping units have at least one master switch at the main entry door that controls wired luminaires and switched receptacles.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Exception: Requirement does not apply.
C405.2.2. [EL18] ¹	Occupancy sensors installed in required spaces.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Requirement will be met.
C405.2.2. [EL20] ¹	Primary sidelighted areas are equipped with required lighting controls.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Exception: Requirement does not apply.
C405.2.2. [EL21] ¹	Enclosed spaces with daylight areas under skylights and rooftop monitors are equipped with required lighting controls.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Exception: Requirement does not apply.
C405.2.3 [EL4] ¹	Separate lighting control devices for specific uses installed per approved lighting plans.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Requirement will be met.
C405.3 [EL19] ¹	Fluorescent luminaires with odd numbered lamp configurations that are with 10 feet center to center (residential) or 12 feet center to edge to edge (if pendant or surface mounted) shall be tandem wired.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Exception: Requirement does not apply.
C405.4 [EL6] ¹	Exit signs do not exceed 5 watts per face.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Requirement will be met.
C405.2.3 [EL8] ¹	Additional interior lighting power allowed for special functions per the approved lighting plans and is automatically controlled and separated from general lighting.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Requirement will be met.

Additional Comments/Assumptions:

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: UNLV MOB Report date: 03/16/16
Data filename: J:\2015\15122 UNLV Maryland Office Building #1 MOB 1\OFFICE\ CALC LTG\IECC\20160316-151 Page 3 of 6
ELECTRICAL.IECC.cck

COMcheck Software Version 4.0.2.8 Inspection Checklist

Energy Code: 2012 IECC

Text in the "Comments/Assumptions" column is provided by the user in the COMcheck Requirements screen. For each requirement, the user certifies that a code requirement will be met and how that is documented, or that an exception is being claimed. Where compliance is itemized in a separate table, a reference to that table is provided.

Section # & Req.ID	Plan Review	Complies?	Comments/Assumptions
C103.2. [PR4] ¹	Plans, specifications, and/or calculations provide all information with which compliance can be determined for the interior lighting and receptacle requirements and document where exceptions to the standard are claimed. Information provided includes fixture type, lighting power calculations, wattage of bulbs and ballasts, transformers and controls.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Requirement will be met.
C406 [PR9] ¹	Plans, specifications, and/or calculations provide all information with which compliance can be determined for the additional energy efficiency package options.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Requirement will be met.

Additional Comments/Assumptions:

1 High Impact (Tier 1) 2 Medium Impact (Tier 2) 3 Low Impact (Tier 3)

Project Title: UNLV MOB Report date: 03/16/16
Data filename: J:\2015\15122 UNLV Maryland Office Building #1 MOB 1\OFFICE\ CALC LTG\IECC\20160316-151 Page 3 of 6
ELECTRICAL.IECC.cck

COMcheck Software Version 4.0.2.8 Interior Lighting Compliance Certificate

Energy Code: 2012 IECC

Project Information
Project Title: UNLV
Project Type: New Construction
Construction Site: LAS VEGAS, NV
Owner/Agent: UNLV
Designer/Contractor: MARIO AL HADDAD
TJK CONSULTING ENGINEERS

Allowed Interior Lighting Power		A Area Category	B Floor Area (ft ²)	C Allowed Watts / ft ²	D Allowed Watts (B x C)
1-Admin Office (Office)			9633	0.85	8168
Total Allowed Watts = 8168					
Proposed Interior Lighting Power		A Fixture ID : Description / Lamp / Wattage Per Lamp / Ballast	B Lamps/ Fixture	C # of Fixtures	D Future Watt. (C x D)
1-Admin Office (Office)		LED 1 F1 2X LED 4000K LED Other Fixture Unit 40W: LED 2 F2 2X LED 4000K LED Other Fixture Unit 36W: LED 3 F3 6" DOWN LIGHT 2X LM LED PAR 18W: LED 4 F4 6" DOWN LIGHT 1X LM LED Other Fixture Unit 36W: LED 5 F5 4" LED STRIP 4000K LED Linear 35W:	1 1 1 1 1	25 38 18 35 23	975 4550 324 245 8160
Total Proposed Watts = 8160					

Interior Lighting PASSES: Design 25% better than code

Interior Lighting Compliance Statement

Compliance Statement: The proposed interior lighting design represented in this document is consistent with the building plans, specifications, and other calculations submitted with this permit application. The proposed interior lighting systems have been designed to meet the 2012 IECC requirements in COMcheck Version 4.0.2.8 and to comply with the mandatory requirements listed in the Inspection Checklist.

Name - Title _____ Signature _____ Date _____

Project Title: UNLV MOB Report date: 03/16/16
Data filename: J:\2015\15122 UNLV Maryland Office Building #1 MOB 1\OFFICE\ CALC LTG\IECC\20160316-151 Page 1 of 6
ELECTRICAL.IECC.cck

Section # & Req.ID	Final Inspection	Complies?	Comments/Assumptions
C408.2.5. [F116] ¹	Furnished as-built drawings for electric power systems within 30 days of system acceptance.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Requirement will be met.
C303.3.C4 [F177] ¹	Furnished OEM instructions for systems and equipment to the building owner or designated representative.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Requirement will be met.
C405.5.2 [F118] ¹	Interior installed lamp and fixture lighting power is consistent with what is shown on the approved lighting plans, demonstrating proposed watts are less than or equal to allowed watts.		See the Interior Lighting fixture schedule for values.
C408.3 [F133] ¹	Lighting systems have been tested to proper calibration, adjustment, programming, and operation.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Requirement will be met.
C406 [F134] ¹	Efficient HVAC performance, efficient lighting system, or on-site supply of renewable energy consistent with what is shown on the approved plans.	<input type="checkbox"/> Complies <input type="checkbox"/> Does Not <input type="checkbox"/> Not Observable <input type="checkbox"/> Not Applicable	Requirement will be met.

Additional Comments/Assumptions:

Project Title: UNLV MOB Report date: 03/16/16
Data filename: J:\2015\15122 UNLV Maryland Office Building #1 MOB 1\OFFICE\ CALC LTG\IECC\20160316-151 Page 5 of 6
ELECTRICAL.IECC.cck

LA VEGAS

KGA ARCHITECTURE

1975 West Diablo Drive, Third Floor
Las Vegas, Nevada 89148
512.441.8200

AUSTIN

PROJECT:
UNLV MARYLAND
ADMINISTRATIVE BUILDING I
TENANT IMPROVEMENT

MECHANICAL / PLUMBING / ELECTRICAL

TJK CONSULTING ENGINEERS, INC.

PHONE: 702.671.3621

www.tjkengineering.com

SHEET:

E0.02

DATE:

APRIL 25, 2016


JOB NO:

16323.00

SHEET:

TJK # 15122





REVISIONS

DEMOLITION GENERAL NOTES:

1. ALL CONDUIT AND WIRING FROM REMOVED DEVICES SHALL BE REMOVED BACK TO SOURCE.
2. ALL LIGHT FIXTURES IN THE BUILDING TO BE REMOVED AND DISPOSED.
3. CONDUIT IN INACCESSIBLE LOCATIONS SHALL BE CAPPED OFF AND TO REMAIN IN PLACE.
4. WIRING SHALL NOT BE ABANDONED IN INACCESSIBLE CONDUITS.
5. ALL SWITCHING AND CONTROL DEVICES TO BE DEMOLISHED. PATCH EXISTING OPENING THAT ARE NOT REUSED.

DEMOLITION SHEET NOTES: #

1. EXISTING CIRCUITS TO BE INTERCEPTED AND EXTENDED TO NEW PANEL AS INDICATED ON E1.01.

UNLV
MARYLAND ADMINISTRATIVE BUILDING I
TENANT IMPROVEMENT


KGA ARCHITECTURE
1701 Directon Boulevard, Suite 770
Austin, Texas 78744
512.441.8200
www.KGArchitects.com


CONSULTANTS:
MECHANICAL / PLUMBING / ELECTRICAL
TJK CONSULTING ENGINEERS, INC.
PHONE 702.871.3621

PROJECT:
UNLV MARYLAND
ADMINISTRATIVE BUILDING I
TENANT IMPROVEMENT

Sheet Contents:
LIGHTING DEMOLITION
PLAN

DATE: APRIL 25, 2016
Job No.: 16323.00
Sheet: E0.03





REVISIONS

DEMOLITION GENERAL NOTES:

1. ALL CONDUIT AND WIRING FROM REMOVED DEVICES SHALL BE REMOVED BACK TO SOURCE.
2. ALL RECEPTACLES TO BE REMOVED. REMOVE J BOXES, CONDUITS AND WIRES BACK TO SOURCE.
3. CONDUIT IN INACCESSIBLE LOCATIONS SHALL BE CAPPED OFF AND TO REMAIN IN PLACE.
4. WIRING SHALL NOT BE ABANDONED IN INACCESSIBLE CONDUITS.
5. PROVIDE UPDATED, TYPED PANEL DIRECTORIES FOR ALL PANEL BOARDS WITH CIRCUITS MODIFIED, ADDED OR REMOVED.

DEMOLITION KEY NOTES: #

1. PROTECT IN PLACE EXISTING DEVICES TO REMAIN.
- 2.

UNLV
MARYLAND ADMINISTRATIVE BUILDING I
TENANT IMPROVEMENT


KGA ARCHITECTURE
1701 Director Boulevard, Suite 770
Austin, Texas 78744
512.441.8200
www.KGAarchitects.com


CONSULTANTS:
MECHANICAL / PLUMBING / ELECTRICAL
TJK CONSULTING ENGINEERS, INC.
PHONE 702.671.3621
www.tjkengineering.com

PROJECT:
UNLV MARYLAND
ADMINISTRATIVE BUILDING I
TENANT IMPROVEMENT

Sheet Contents:
POWER DEMOLITION PLAN

DATE: APRIL 25, 2016
Job No.: 16323.00
Sheet: E0.04





DEMOLITION GENERAL NOTES:

1. ALL EXISTING DATA OUTLETS SHOWN ARE TO BE REMOVED UNLESS NOTED OTHERWISE. WHERE EXISTING DATA OUTLETS ARE INSTALLED IN SURFACE MOUNTED WIRE MOLD, REMOVE WIRE MOLD AND CABLE. WHERE EXISTING DATA OUTLETS ARE INSTALLED RECESSED IN WALL, REMOVE EXISTING CABLING AND PROVIDE BLANK COVER PLATE. ALSO SEE GENERAL NOTE #4 FOR ADDITIONAL WORK.
2. COORDINATE WITH UNLV ON ALL NETWORK OUTAGES AT LEAST 48 HOURS BEFORE THE CHANGE IS TO OCCUR.
3. THE CONTRACTOR SHALL VISIT THE SITE IN ORDER TO BECOME FAMILIAR WITH THE EXISTING CONDITIONS AND TO PERFORM ALL REQUIRED STUDIES DEEMED NECESSARY.
4. ALL REPAIRING, PATCHING AND PAINTING OF ANY WALL MODIFIED SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.

UNLV
MARYLAND ADMINISTRATIVE BUILDING I
TENANT IMPROVEMENT

KGA ARCHITECTURE
1701 Director Boulevard, Suite 770
Austin, Texas 78744
512.441.8200
www.KGArchitects.com


CONSULTANTS:
MECHANICAL / PLUMBING / ELECTRICAL
TJK CONSULTING ENGINEERS, INC.
PHONE: 702.671.3621


PROJECT:
UNLV MARYLAND
ADMINISTRATIVE BUILDING I
TENANT IMPROVEMENT

Sheet Contents:
LOW-VOLTAGE DEMOLITION PLAN

DATE: APRIL 25, 2016
Job No.: 16323.00
Sheet: 1

TK CONSULTING ENGINEERS, INC.
5459 S. Durango Dr., Suite 100
Las Vegas, NV 89113
P: 702.671.3621
F: 702.671.8253
www.tkjengineers.com






REVISIONS

POWER GENERAL NOTES:

- REFER TO MECHANICAL AND PLUMBING DRAWINGS FOR EQUIPMENT LOCATION AND REQUIREMENTS.
- ALL RECEPTACLES AND OUTLETS LOCATED ON FURNITURE SHALL BE COORDINATED WITH ARCHITECTURAL DRAWINGS PRIOR TO ROUGH-IN.
- VERIFY EXACT LOCATIONS OF ALL EQUIPMENT PER ARCHITECTURAL DRAWINGS.
- ALL EXTERIOR DISCONNECTS SHALL BE NEMA-3R RATED.
- EXTERIOR RECEPTACLES SHALL BE IN-USE WEATHER PROOF.
- REFER TO SINGLE LINE DIAGRAM FOR FEEDER AND EQUIPMENT SIZES.

POWER KEY NOTES: (1)

- PROVIDE POWER FOR TV.
- RFBB SERIES FLOORBOX, FOR POWER AND DATA CABLES, SAWCUT, TRENCH AND BACKFILL AS REQUIRED.



UNLV
MARYLAND ADMINISTRATIVE BUILDING I
TENANT IMPROVEMENT

KGA ARCHITECTURE
1701 Director Boulevard, Suite 770
Austin, Texas 78744
512.441.8200
www.kgarchitects.com


CONSULTANTS:
MECHANICAL / PLUMBING / ELECTRICAL
TJK CONSULTING ENGINEERS, INC.
PHONE 702.671.3621
702.367.6900
www.tjkengineering.com

PROJECT:
UNLV MARYLAND
ADMINISTRATIVE BUILDING I
TENANT IMPROVEMENT

Sheet Contents:
POWER PLAN

DATE: APRIL 25, 2016
Job No.: 16323.00
Sheet: E2.01

tk
tk consulting engineers, inc.
5459 S. Durango Dr., Suite 100
Las Vegas, NV 89113
P: 702.671.3621
F: 702.671.8253
www.tkjengineering.com
TJK # 15122



REVISIONS:

UNLV

MARYLAND ADMINISTRATIVE BUILDING I

TENANT IMPROVEMENT

KGA ARCHITECTURE
1701 Directors Boulevard, Suite 770
Austin, Texas 78744
512.441.8200
www.KGArchitects.com


CONSULTANTS:
MECHANICAL / PLUMBING / ELECTRICAL
TJK CONSULTING ENGINEERS, INC.
PHONE: 702.671.3621
FAX: 702.671.3600
www.tjkengineering.com

PROJECT:
UNLV MARYLAND
ADMINISTRATIVE BUILDING I
TENANT IMPROVEMENT

SHEET CONTENTS:
COMMUNICATION PLAN

DATE:
APRIL 25, 2016
JOB NO.:
16323.00
SHEET:

E3.01




COMMUNICATIONS GENERAL NOTES:

- ALL CURRENT FLOOR BOXES ARE TO REMAIN, UNLESS OTHERWISE NOTED
- ALL CURRENT ELECTRICAL AND DATA LOCATIONS TO REMAIN AS IS, UNLESS OTHERWISE NOTED
- FOR ALL POWER AND DATA TO BE INSTALLED WITHIN THE EXISTING DUCT AND CELLULAR FLOOR, THE CONTRACTOR SHALL COORDINATE THE REMOVAL AND REINSTALLATION OF ALL FLOORING AS NEEDED TO ACCESS THE DISTRIBUTION SYSTEM
- ALL FLOOR BOX INSTALLATION REQUIRE AN X-RAY OF THE FLOOR PRIOR TO THE START OF ANY WORK
- FOR THE REQUIREMENTS ON ROUTING AND SUPPORT OF ALL LOW VOLTAGE CABLE REFER TO THE SPECIFICATION HERE (http://oit.unlv.edu/sites/default/files/campus_wiring_standards_8-26-15_1.pdf)

COMMUNICATIONS KEY NOTES: (1)

- FLOOR BOX OUTLET - PROVIDE A 1" CONDUIT FROM THE FLOOR BOX TO THE NEAREST WALL THEN TO THE CEILING SPACE ABOVE. REFER TO THE ELECTRICAL SHEETS FOR THE FLOOR BOX TYPE. PROVIDE CAT 6A DATA CABLES QTY AS INDICATED AND ROUTE THE CABLE TO THE TR ROOM #113.
- DATA FURNITURE J-BOX - PROVIDE (1) 1 1/4" CONDUIT FROM THE FURNITURE TO THE CEILING SPACE ABOVE. PROVIDE CAT 6A DATA CABLES QTY AS INDICATED FOR EACH STATION AND ROUTE THE CABLE TO THE TR ROOM #113.
- FURNITURE OUTLET PROVIDE A 4-PORT MODULAR FURNITURE FACE PLATE AT EACH LOCATION COORDINATE WITH THE FURNITURE SUPPLIER. AS TO WHICH FACEPLATES ARE REQUIRED. TERMINATE EACH CABLE AS INDICATED.
- DATA OUTLET - PROVIDE A 1" CONDUIT TO THE CEILING SPACE WITH A 4 11/16" EXTRA DEEP J-BOX AND A SINGLE GANG MUD RING. PROVIDE CAT 6A DATA CABLES QTY AS INDICATED AND ROUTE THE CABLE TO THE TR ROOM #113.
- NEW CEILING MOUNTED WIRELESS LOCATION - CONTRACTOR SHALL INSTALL TWO (2) CAT 6A WITH A 4 11/16" EXTRA DEEP J-BOX AND A SINGLE GANG MUD RING. COORDINATE THE EXACT LOCATION PRIOR TO INSTALLATION. ROUTE THE CABLE TO THE TR ROOM #113. REFER TO DETAIL SHEET E4XX FOR ADDITIONAL INFORMATION.
- CONTRACTOR REQUIRED TO X-RAY AND SAW CUT THE FLOOR AS REQUIRED TO INSTALL THE CONDUIT AND FLOOR BOXES REFER TO THE ARCHITECTURAL DETAIL FOR ADDITIONAL INFORMATION.
- PROVIDE A 4 11/16" JUNCTION BOX, A SINGLE GANG MUD RING AND A 1" CONDUIT ROUTED DOWN TO THE FLOOR ALSO TO THE CEILING SPACE ABOVE SEE DETAILS SHEET E401 FOR ADDITIONAL INFORMATION.



REVISIONS:


SHEET NOTES

- EXISTING INCOMING SERVICES
- CHATSWORTH WALL ANGLE SUPPORT (PART# 11421-718) FOR 18" W LADDER TRAY, BLACK
- CHATSWORTH TRIANGLE SUPPORT BRACKET (PART# 11746-718) FOR 18" W LADDER TRAY, BLACK
- CHATSWORTH LADDER TRAY (PART# 10250-718) UNIVERSAL CABLE RUNWAY, 18" W, BLACK
- CHATSWORTH CORNER BRACKET (PART# 11959-715) 15" RADIUS, BLACK
- CHATSWORTH LADDER TRAY (PART# 31472-718) ALTERNATE SPACE CABLE RUNWAY, 18" W, BLACK
- CHATSWORTH END CLOSING KIT (PART# 11700-718) FOR 18" W LADDER TRAY, BLACK
- EXISTING PLYWOOD BACKBOARD TO REMAIN
- EXISTING CABINET OR 2 POST RACK TO BE REMOVED AND DISPOSED OF
- PROVIDE ADDITIONAL PLYWOOD TO MATCH EXISTING.
- EXISTING ELECTRICAL PANEL REFER TO THE ELECTRICAL POWER SHEETS FOR ADDITIONAL INFORMATION.

UNLV
MARYLAND ADMINISTRATIVE BUILDING I
TENANT IMPROVEMENT

GENERAL NOTES



- CONDUIT FOR ELECTRICAL SERVICES WITHIN ANY ER/ TR LOCATION SHALL BE INSTALLED BEHIND THE PLYWOOD BACKBOARD OR GYPSUM BOARD. THIS CONDUIT SHALL NEVER BE SURFACE MOUNTED.
- AS REQUIRED BY DESIGN, CONDUIT FOR SURFACE MOUNTED FLOOR BOXES SHALL BE ROUTED UNDER THE CONCRETE SLAB FROM THE ELECTRICAL SUBPANEL TO THE SPECIFIC LOCATION SHOWN IN THE DETAIL DRAWINGS.
- AS REQUIRED BY DESIGN, CONDUIT FOR SURFACE MOUNTED FLOOR BOXES SHALL BE ROUTED RECESSED IN WALL FROM THE ELECTRICAL SUB PANEL TO THE SPECIFIC LOCATION SHOWN IN THE DETAIL DRAWINGS.
- CONDUIT FOR DATA AND/OR TELEPHONE CABLE WITHIN ANY ER/TR LOCATION SHALL BE INSTALLED BEHIND THE PLYWOOD BACKBOARD OR GYPSUM BOARD. THIS CONDUIT SHALL NEVER BE SURFACE MOUNTED.
- BACKBOARD SHALL BE PLACED VERTICALLY, MOUNTED AT +12" AFF AND SHALL EXTEND TO +108" AFF.
- PLACEMENT OF EXTERNAL ELECTRICAL SUBPANELS AND CUT OFF SWITCHES SHALL BE COORDINATED WITH THE OWNER PRIOR TO PLACEMENT. AT NO TIME SHALL THE PLACEMENT OF THESE ITEMS INTERFERE WITH THE LAYOUT OF THE ROOM OR ASIGNED BACKBOARD SPACES.
- THE CONTRACTOR SHALL PROVIDE AND INSTALL ALL MATERIALS IDENTIFIED IN THESE DETAIL DRAWINGS AND ALL ADDITIONAL MATERIALS REQUIRED FOR THE SUCCESSFUL INSTALLATION OF THE LOW VOLTAGE SYSTEMS IN THE ER/TR SPACES.
- REFER TO CONSTRUCTION INSTALLATION REQUIREMENTS (E4.40) FOR ADDITIONAL INFORMATION.
- (E) - INDICATES EXISTING DEVICE TO REMAIN. (NL) - INDICATES NEW LOCATION OF DEVICE OR LIGHT FIXTURE. REMOVE LIGHT FIXTURE, STORE, CLEAN, RELAMP AND INSTALL IN NEW LOCATION. EXTEND CONDUIT AND WIRE AS REQUIRED.



ROOM #	ROOM DESCRIPTION	WIRELESS ACCESS	LOCATIONS			CAT 6 Blue	IT CLOSET #
			CEILING MOUNTED	FLOOR BOXES	FURNITURE OUTLETS		
SHEET # E3.01							
107	CO-DIRECTOR (CEILING)	1	1			1	IT# 113
107	CO-DIRECTOR (WALL)			1		2	IT# 113
108	MEETING AREA (FLOOR)				1	2	IT# 113
109	CO-DIRECTOR (WALL)				2	2	IT# 113
114	OPEN OFFICE (CEILING)	3	3		1	3	IT# 113
114	OPEN OFFICE (FLOOR)			3		4	IT# 113
114	OPEN OFFICE (WORK STATIONS)				20	4	80 IT# 113
104	ASSISTANT DIRECTOR (WALL)				2	2	IT# 113
103	ADMINISTRATOR (WALL)				3	2	IT# 113
102	STUDIO (WALL)				2	2	IT# 113
115	COPY (WALL)				3	2	IT# 113
101	LOBBY (CEILING)	1	1		1	1	IT# 113
101	LOBBY (WALL)				5	2	10 IT# 113
101	LOBBY (COUNTER)				2	2	4 IT# 113
128	CONFERENCE ROOM (CEILING)	1	1			1	IT# 113
128	CONFERENCE ROOM (FLOOR)			1		2	IT# 113
128	CONFERENCE ROOM (WALL)				1	2	IT# 113
131	MEETING ROOM (CEILING)	1	1			1	IT# 113
131	MEETING ROOM (FLOOR)			1		2	IT# 113
131	MEETING ROOM (WALL)				2	2	IT# 113
130	MEETING ROOM (CEILING)	1	1		1	1	IT# 113
130	MEETING ROOM (FLOOR)			1		2	IT# 113
130	MEETING ROOM (WALL)				2	2	4 IT# 113
127	VIDEO STUDIO (WALL)	1	1			4	IT# 113
127	VIDEO STUDIO (FLOOR)					1	IT# 113
120	OPEN OFFICE (CEILING)	1	1			4	IT# 113
120	OPEN OFFICE (WORK STATIONS)				4	4	16 IT# 113
TOTALS IT 113		10	10	7	26	33	196

4 ROOM LIST MATRIX

SCALE: NONE




6 NEW RACK DETAILS


SCALE: NONE

5 TOP VIEW NEW FLOOR BOX

SCALE: NONE



SIDE VIEW



FRONT VIEW

5 TOP VIEW NEW FLOOR BOX

SCALE: NONE

KGA ARCHITECTURE
1075 West Diablo Drive, Third Floor
Las Vegas, Nevada 89148
512.441.8200
www.kgarchitects.com


CONSULTANTS:
MECHANICAL / PLUMBING / ELECTRICAL
TJK CONSULTING ENGINEERS, INC.
PHONE 070 871-3621

PROJECT:
UNLV MARYLAND
ADMINISTRATIVE BUILDING I
TENANT IMPROVEMENT

SHEET CONTENTS
ENLARGED PLANS AND DETAILS

DATE:
APRIL 25, 2016
JOB NO:
16323.00
SHEET:


E4.01



GENERAL NOTES:

1. THE PROFESSIONAL HAS PERFORMED ALL REQUIRED VOLTAGE DROP CALCULATIONS AND ALL BRANCH CIRCUITS AND FEEDER COMPLY WITH NEC 210.19(A)(1).

REVISIONS:



PARTIAL ELECTRICAL ONELINE DIAGRAM

NOT TO SCALE

EXISTING PANEL A		VOLTAGE 120/240V		ENCLOSURE TYPE: NEMA 1	
LOCATION	ELECTRICAL CLOSET	PHASES: SINGLE	WIRING: THREE	MOUNTING: EXISTING	A/C RATING (A): 10,000
SUPPLY FROM	DB				
MIN. BUS CAPACITY (A):	200				
MAIN BREAKER	NO				
NOTES: PANEL SHOWN FOR CLARITY ONLY					
NOTES	CKT	LOAD	CKT	LOAD	NOTES
	CKT	BRK	CONNECTED LOAD (VA)	CKT	LOAD
	CKT	BRK	TRIP	CKT	TRIP
1.1	SPARE	20	A	20	OUTLET R 2 1
1.3	SPARE	20	B	20	SPARE 4 1
1.5	SPARE	20	A	20	SPARE 6 1
1.7	SPARE	20	B	20	OUTLET R 7 1
1.9	R OUTLETS	20	A	20	LIGHTING 10 1
1.11	R OUTLETS	20	B	20	OUTLETS R 12 1
1.13	SPARE	20	A	20	OUTLETS R 14 1
1.15	R OUTLETS	20	B	20	OUTLETS R 16 1
1.17	R OUTLETS	20	A	20	OUTLETS R 18 1
1.19	SPARE	20	B	20	OUTLET R 20 1
1.21	R OUTLETS	20	A	20	OUTLET R 22 1
1.23	R OUTLETS	20	B	20	OUTLET R 24 1
1.25	R OUTLETS	20	A	20	OUTLET R 26 1
1.27	L OUTSIDE LIGHTING	20	B	20	OUTLET R 28 1
1.29	L OUTSIDE LIGHTING	20	A	20	OUTLET R 30 1
1.31	R OUTLETS	20	B	20	FIRE ALARM PANEL F 32 1
1.33	L OUTSIDE LIGHTING	20	B	20	OUTLET R 34 1
1.35	ROOF A/C	20	A	20	OUTLET R 36 1
1.37	R OUTLETS	20	B	20	OUTLET R 38 1
1.39	R OUTLETS	20	A	20	OUTLET R 40 1
1.41	R OUTLETS	20	B	20	OUTLET R 42 1
NOTES: CONNECTED PANEL (S) LOADS INCLUDED ABOVE					
	CONNECTED VA		DEMAND VA		
TOTAL RECEPTACLE(R)	0	0%	0		
TOTAL MOTOR (M) LOAD	0	0%	0		
TOTAL LIGHTING (L) LOAD @ 125%	0	0%	0		
TOTAL KITCHEN (K) LOAD @100%	0	0%	0		
TOTAL OTHER (O) LOAD	0	0%	0		
TOTAL ELEVATOR (EL) LOAD @ 100%	0	0%	0		
NOTES: CONNECTED PANEL (S) LOADS INCLUDED ABOVE	TOTAL	0	0		
1. EXISTING BREAKER 2. PROVIDE SHUNT TRIP DEVICE 3. PROVIDE GFO DEVICE 4. PROVIDE RED CIRCUIT BREAKER 5. PROVIDE SUB-FEED BREAKER 6. CONTROLLED VIA RELAY				7. EXISTING LOAD REMOVED, REUSE EXISTING BREAKER 8. CIRCUIT BREAKER CONTROLLED BY OTHER EQUIPMENT 9. PROVIDE NEW BREAKER, MOUNTING HARDWARE, MATCH TYPE AND A/C RATING.	

EXISTING PANEL B		VOLTAGE 120/240V		ENCLOSURE TYPE: NEMA 1	
LOCATION	ELECTRICAL CLOSET	PHASES: SINGLE	WIRING: THREE	MOUNTING: EXISTING	A/C RATING (A): 10,000
SUPPLY FROM	DB				
MIN. BUS CAPACITY (A):	200				
MAIN BREAKER	NO				
NOTES: PANEL SHOWN FOR CLARITY ONLY					
NOTES	CKT	LOAD	CKT	LOAD	NOTES
	CKT	BRK	CONNECTED LOAD (VA)	CKT	LOAD
	CKT	BRK	TRIP	CKT	TRIP
1.1	L	EXISTING EXTERIOR LIGHTS	20	A	30
1.3	L	FLOOR PLUGS	20	B	20
1.5	L	FLOOR PLUGS	20	A	20
1.7	L	FLOOR PLUGS	20	B	20
1.9	R	COPPER	20	A	19
1.11	R	FLOOR PLUGS	20	B	20
1.13	R	FLOOR PLUGS	20	A	19
1.15	R	FLOOR PLUGS	20	B	20
1.17	R	FLOOR PLUGS	20	A	19
1.19	R	COPPER	20	B	20
1.21	R	OUTLETS	20	A	20
1.23	R	OUTLETS	20	B	20
1.25	R	OUTLETS	20	A	20
1.27	L	OUTSIDE LIGHTING	20	B	20
1.29	L	OUTSIDE LIGHTING	20	A	20
1.31	R	OUTLETS	20	B	20
1.33	L	OUTSIDE LIGHTING	20	B	20
1.35	ROOF A/C	20	A	20	OUTLET R 36 1
1.37	R	OUTLETS	20	B	20
1.39	R	OUTLETS	20	A	20
1.41	R	OUTLETS	20	B	20
NOTES: CONNECTED PANEL (S) LOADS INCLUDED ABOVE					
	CONNECTED VA		DEMAND VA		
TOTAL RECEPTACLE(R)	0	0%	0		
TOTAL MOTOR (M) LOAD	0	0%	0		
TOTAL LIGHTING (L) LOAD @ 125%	0	0%	0		
TOTAL KITCHEN (K) LOAD @100%	0	0%	0		
TOTAL OTHER (O) LOAD	0	0%	0		
TOTAL ELEVATOR (EL) LOAD @ 100%	0	0%	0		
NOTES: CONNECTED PANEL (S) LOADS INCLUDED ABOVE	TOTAL	0	0		
1. EXISTING BREAKER 2. PROVIDE SHUNT TRIP DEVICE 3. PROVIDE GFO DEVICE 4. PROVIDE RED CIRCUIT BREAKER 5. PROVIDE SUB-FEED BREAKER 6. CONTROLLED VIA RELAY				7. EXISTING LOAD REMOVED, REUSE EXISTING BREAKER 8. CIRCUIT BREAKER CONTROLLED BY OTHER EQUIPMENT 9. PROVIDE NEW BREAKER, MOUNTING HARDWARE, MATCH TYPE AND A/C RATING.	

EXISTING PANEL D		VOLTAGE 120/240V		ENCLOSURE TYPE: NEMA 1	
LOCATION	ELECTRICAL CLOSET	PHASES: SINGLE	WIRING: THREE	MOUNTING: EXISTING	A/C RATING (A): 10,000
SUPPLY FROM	DB				
MIN. BUS CAPACITY (A):	100				
MAIN BREAKER	NO				
NOTES: PANEL SHOWN FOR CLARITY ONLY					
NOTES	CKT	LOAD	CKT	LOAD	NOTES
	CKT	BRK	CONNECTED LOAD (VA)	CKT	LOAD
	CKT	BRK	TRIP	CKT	TRIP
1.1	L	EXISTING EXTERIOR LIGHTS	20	A	30
1.3	L	FLOOR PLUGS	20	B	20
1.5	L	FLOOR PLUGS	20	A	20
1.7	R	COPPER	20	B	20
1.9	R	ROOF RECEPTACLES	20	A	20
1.11	R	ROOF RECEPTACLES	20	B	20
1.13	R	R OUTLETS	20	A	19
1.15	R	FLOOR PLUGS	20	B	20
1.17	R	COPPER	20	A	19
1.19	R	OUTLETS	20	B	20
1.21	R	OUTLETS	20	A	20
1.23	R	OUTLETS	20	B	20
1.25	R	OUTLETS	20	A	20
1.27	L	OUTSIDE LIGHTING	20	B	20
1.29	L	OUTSIDE LIGHTING	20	A	20
1.31	R	OUTLETS	20	B	20
1.33	L	OUTSIDE LIGHTING	20	B	20
1.35	ROOF A/C	20	A	20	OUTLET R 36 1
1.37	R	OUTLETS	20	B	20
1.39	R	OUTLETS	20	A	20
1.41	R	OUTLETS	20	B	20
NOTES: CONNECTED PANEL (S) LOADS INCLUDED ABOVE					
	CONNECTED VA		DEMAND VA		
TOTAL RECEPTACLE(R)	0	0%	0		
TOTAL MOTOR (M) LOAD	0	0%	0		
TOTAL LIGHTING (L) LOAD @ 125%	0	0%	0		
TOTAL KITCHEN (K) LOAD @100%	0	0%	0		
TOTAL OTHER (O) LOAD	0	0%	0		
TOTAL ELEVATOR (EL) LOAD @ 100%	0	0%	0		
NOTES: CONNECTED PANEL (S) LOADS INCLUDED ABOVE	TOTAL	0	0		
1. EXISTING BREAKER 2. PROVIDE SHUNT TRIP DEVICE 3. PROVIDE GFO DEVICE 4. PROVIDE RED CIRCUIT BREAKER 5. PROVIDE SUB-FEED BREAKER 6. CONTROLLED VIA RELAY				7. EXISTING LOAD REMOVED, REUSE EXISTING BREAKER 8. CIRCUIT BREAKER CONTROLLED BY OTHER EQUIPMENT 9. PROVIDE NEW BREAKER, MOUNTING HARDWARE, MATCH TYPE AND A/C RATING.	

PANEL E		VOLTAGE 120/240V		ENCLOSURE TYPE: NEMA 1	
LOCATION	ELECTRICAL CLOSET	PHASES: SINGLE	WIRING: THREE	MOUNTING: SURFACE	A/C RATING (A): 10,000

<tbl_r cells="3" ix="1" maxcspan="2" maxrspan