

LIGHTING POSITIONS

pipes of the stretch wire grid.

CONTROL BOOTH

Lighting is accomplished by attaching short pipes to the supporting

Located on the second floor the booth, it houses separate areas for

BLACK BOX THEATRE FACT SHEET

| GENERAL | sound, lights and stage manager. |
|--|---|
| The Black Box Theatre is located in the Alta Ham Fine Arts complex, which is located on the campus of the University of Nevada, Las Vegas. The 140-175 maximum seat facility was constructed in 1983. AUDITORIUM | DIMMERS The dimmer system was manufactured by Strand Century and consists of 140 - 2.4 kw (CD-80). The lighting load circuits are hard-wired to dimmers and patching is by means of "soft-patching" through the control board. |
| The space can seat up to 175 on individual padded chairs (in an arena configuration). There are 48 Rosco "Vario" Nivoflex risers. The heights are 8", 16", 24", and 32". | CONTROL BOARD ETC Express 24 subs with programmable codes. |
| LOBBY | CABLE INVENTORY |
| The main lobby is small and is located in the foyer of the Alta Ham Fine Arts complex. | Connectors are NEMA LP-20P grounded Twist-Lock. This inventory is shared by the Black Box Theatre, the Judy Bayley Theatre, and the Paul Harris Theatre. Its availability is subject to |
| BOX OFFICE The Black Box Theatre shares the Performing Arts Center Box Office, which is located by the Artemus W. Ham Concert Hall and the UNLV North Parking Garage. | use by the Department of Theatre. COMPANY SWITCH The company switch is located in the control booth. Available |
| REGULATIONS Smoking is not permitted in the facility. The customary curtain times are 2:00 pm and 8:00 pm. All house equipment must be | power is 3-phase, 4-wire, 80 amps, 120/220 v, 60 hz. Connection is with lugs. FOLLOW SPOTLIGHTS The building has no followspots. |
| operated by house technicians. | |
| LOADING The load-in area has a slight grade and can accommodate one medium sized vehicle at a time. The loading door is 10'-0" high and 9'-10" wide. | SOUND CONTROL SYSTEM |
| The stage space (including the auditorium) is 46'-1" x 46'-2" with | Tape Recorders/Reproducers: Denon CD/Tape Deck; Sony CD; Dual Tape Professional |
| perimeter aisles and masking drapes surrounding all sides. The height is 21'-0" from the floor to the stretch wire grid. There is a second floor walkway and railing on three sides. The walkway is 14'-0" from the stage and 8'-2" wide. The balcony railing is 3'-1" high. | PERFORMERS' AREA The performers' wing located adjacent to the stage houses the green room and dressing rooms. The green room contains limited kitchen facilities and seating for approximately 15 people. The men's and women's dressing rooms contain makeup stations for 5 persons |
| STAGE FLOOR | each as well as sinks, toilets and showers. |
| The stage floor is masonite over edge grain pine, over 2 rows of sleepers, over concrete. The masonite is painted black. | MICROPHONES All microphone and line-level connections are made with 3-pin |
| RIGGING SYSTEM | XLR professional audio connectors. There are a limited number |
| Only limited rigging can be done off the stretch wire grid. The facility has no rigging hardware. | of adapters available. *Dynamic Microphones: 1 Electro-Voice 635A omnidirectional, |

2 Electro-Voice RE55 omnidirectional, 4 Electro-Voice RE16

Condenser Microphones: the condenser microphones are all

part of the AKG C451E and five 451 EB preamplifiers, 6 CK1 cardioid capsules, 8 CK2 omnidirectional capsules and 7 CK9

directional "shotgun" attachments. Phantom power is supplied

cardioid, 2 Shure 570 lavaliere.

to the microphones from the mixer console.